

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 1/23



Issued by: SK

Confirmed by: GL

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Productname	<b>Kelfort</b> ® Industrial spray
Article number	1513231-57, 1513260
Producttype	Spray
Regulation	REACH (EG) regulation nr. 1907/2006 - nr. 2020/878
UFI- code	GS00-V0W2-M00D-09VY

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Paint in aerosol form. For professional use only.
Uses advised against	All such use is not specified in this section, not in section 7.3.

### 1.3 Details of the supplier of the safety data sheet

**Distributeur** Ferney Group BV  
Postbus 24  
1700 AA Heerhugowaard – The Netherlands  
T +31 (0)72-5765000 - F +31 (0)72-5765010  
[bedrijfsbureau@ferneygroup.nl](mailto:bedrijfsbureau@ferneygroup.nl) - [www.ferney.nl](http://www.ferney.nl)

### 1.4 Emergency telephone number

Noodtelefoon : +49(0)9366-907126 (ma-do 7.15-18.00 hour) or  
: +31(0)88-7558000 (after worktime, exclusive use for doctors, pharmacists and government institutions)

Country	Organisation/ Company	Address	Emergency number	Comments
The Netherlands	National Poisons Information Center	House post number B.00.118 PO Box 85500 3508 GA Utrecht	+31 88 755 80 00	For the sole purpose of informing healthcare professionals in the event of acute poisoning

## SECTION 2 : HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Repeated exposure may cause skin dryness or cracking (EUH066).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

The propellant gas is not taken into account when determining the health and environmental classification of the mixture.

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 2/23



Issued by: SK

Confirmed by: GL

## 2.2. Label elements

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07

Signal Word :

DANGER

Product identifiers :

EC 200-662-2

ACETONE

EC 204-658-1

N-BUTYL ACETATE

EC 205-500-4

ETHYL ACETATE

Hazard statements :

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read carefully and follow all instructions.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211

Do not spray on an open flame or other ignition source.

P251

Do not pierce or burn, even after use.

P261

Avoid breathing spray.

P271

Use only outdoors or in a well-ventilated area.

Precautionary statements - Response :

P304 + P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312

Call a POISON CENTER/doctor/... if you feel unwell.

P337 + P313

If eye irritation persists: Get medical advice/attention.

Precautionary statements - Storage :

P410 + P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements - Disposal :

P501

Dispose of contents / container in accordance with national regulations

## 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq$  0.1% published by the European Chemicals Agency (ECHA) under article 59 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances  $\geq$  0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
 VVFK(E) : 01/1513231 -57, 1513260  
 Rev : B  
 Page : 3/23



Isseud by: SK	Confirmed by: GL
---------------	------------------

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

#### Composition :

Identification	Classification (EC) 1272/2008	Note	%
INDEX: ITALIA_00001 CAS: 68476-40-4 EC: 270-681-9 REACH: 01-2119486557-22  HYDROCARBONS, C3-C4 (PROPANE, BUTANE, ISOBUTANE)	GHS02 Flam. Gas 1A, H220 Press. Gas, H280	K [vii]	25 <= x % < 50
INDEX: ITALIA_00002 CAS: 67-64-1 EC: 200-662-2 REACH: 01-2119471330-49-XXXX  ACETONE	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[i]	10 <= x % < 25
INDEX: ITALIA_00004 CAS: 123-86-4 EC: 204-658-1 REACH: 01-2119485493-29  N-BUTYL ACETATE	GHS07, GHS02 Wng Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[i]	10 <= x % < 25
INDEX: ITALIA_00003 CAS: 141-78-6 EC: 205-500-4 REACH: 01-2119475103-46  ETHYL ACETATE	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[i]	2.5 <= x % < 10
INDEX: 022_006_00_2 CAS: 13463-67-7 EC: 236-675-5  TITANIUM DIOXIDE [IN POWDER FORM CONTAINING 1 % OR MORE OF PARTICLES WITH AERODYNAMIC DIAMETER <= 10 µM]		[i]	2.5 <= x % < 10
INDEX: ITALIA_00039 CAS: 1330-20-7 EC: 215-535-7 REACH: 01-2119488216-32-0000  XILENE (BENZENE <0.01%)	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412	[i]	2.5 <= x % < 10
INDEX: ITALIA_00005 CAS: 108-65-6 EC: 203-603-9 REACH: 01-2119475791-29  2-METHOXY-1-METHYLETHYL ACETATE	GHS07, GHS02 Wng Flam. Liq. 3, H226 STOT SE 3, H336	[i]	0 <= x % < 2.5

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 4/23



Isseud by: SK	Confirmed by: GL
---------------	------------------

## Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: ITALIA_00001 CAS: 68476-40-4 EC: 270-681-9 REACH: 01-2119486557-22  HYDROCARBONS, C3-C4 (PROPANE, BUTANE, ISOBUTANE)		inhalation: ATE = 1443 mg/1 (dust/mist)
INDEX: ITALIA_00002 CAS: 67-64-1 EC: 200-662-2 REACH: 01-2119471330-49-XXXX  ACETONE		inhalation: ATE = 76 mg/1 4h (vapours) oral: ATE = 5800 mg/kg BW
INDEX: ITALIA_00004 CAS: 123-86-4 EC: 204-658-1 REACH: 01-2119485493-29  N-BUTYL ACETATE		inhalation: ATE = 21 mg/1 (dust/mist)
INDEX: ITALIA_00039 CAS: 1330-20-7 EC: 215-535-7 REACH: 01-2119488216-32-0000  XILENE (BENZENE <0.01%)		inhalation: ATE = 20 mg/1 (dust/mist) oral: ATE = 5267 mg/kg BW
INDEX: ITALIA_00005 CAS: 108-65-6 EC: 203-603-9 REACH: 01-2119475791-29  2-METHOXY-1-METHYLETHYL ACETATE		inhalation: ATE = 37 mg/1 4h (dust/mist)

## Information on ingredients :

(Full text of H-phrases: see section 16)

[i] Substance for which maximum workplace exposure limits are available.

[vii] Propellant gas

Note K: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of 1,3-butadiene (EINECS 203-450-8).

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

### 4.1. description of first aid measures

#### In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

#### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

# **Safety data sheets Ferney Group BV**

**Date** : 27-03-2026  
**VVFK(E)** : 01/1513231 -57, 1513260  
**Rev** : B  
**Page** : 5/23



Issued by: SK

Confirmed by: GL

## **In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

## **In the event of swallowing :**

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

## **4.2. Most important symptoms and effects, both acute and delayed**

No data available.

## **4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

## **SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

### **5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### **Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

#### **Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

### **5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

### **5.3. Advice for firefighters**

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 6/23



Isseud by: SK

Confirmed by: GL

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

#### Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

#### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 7/23



Issued by: SK

Confirmed by: GL

Provide vapor extraction at the emission source and also general ventilation of the premises.  
Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.  
In all cases, recover emissions at source.  
Avoid skin and eye contact with this mixture.  
Packages which have been opened must be reclosed carefully and stored in an upright position.

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

#### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

#### Storage

Keep out of reach of children.  
Keep the container tightly closed in a dry, well-ventilated place.  
Keep away from all sources of ignition - do not smoke.  
Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

#### Packaging

Always keep in packaging made of an identical material to the original.

#### 7.3. Specific end use(s)

No data available.

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Occupational exposure limits :

- European Union :

CAS	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Notes
67-64-1 ACETONE	1210	500	-	-	-
123-86-4 N-BUTYL ACETATE	241	50	723	150	-
141-78-6 ETHYL ACETATE	734	200	1468	400	-
1330-20-7 XILENE (BENZENE <0.01%)	221	50	442	100	-
108-65-6 2-METHOXY-1-METHYLETHYL ACETATE	275	50	550	100	-

- France :

CAS	VME-ppm	VME-mg/m3	VLE-ppm	VLE-mg/m3	Notes	TMP No
67-64-1 ACETONE	500	1210	1000	2420	VLRC	84
123-86-4 N-BUTYL ACETATE	50	241	150	723	VLRC	84
141-78-6 ETHYL ACETATE	200	734	400	1468	VLRC	84

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
 VVFK(E) : 01/1513231 -57, 1513260  
 Rev : B  
 Page : 8/23



Isseud by: SK	Confirmed by: GL
---------------	------------------

13463-67-7 TITANIUM DIOXIDE [IN POWDER FORM CONTAINING 1 % OR MORE OF PARTICLES WITH AERODYNAMIC DIAMETER <= 10 µM]		10				
1330-20-7 XILENE (BENZENE <0.01%)	50	221	100	442	VLRC	84,4 BIS
108-65-6 2-METHOXY-1-METHYLETH YL ACETATE	50	275	100	550	VLRC	

- Italy :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
67-64-1 ACETONE	500 ppm 1210 mg/m3				
123-86-4 N-BUTYL ACETATE	50 ppm 241 mg/m3	150 ppm 723 mg/m3			
141-78-6 ETHYL ACETATE	200 ppm 734 mg/m3	400 ppm 1468 mg/m3			
1330-20-7 XILENE (BENZENE <0.01%)	50 ppm 221 mg/m3	100 ppm 442 mg/m3			

108-65-6 2-METHOXY-1-METHYLETH YL ACETATE	50 ppm 275 mg/m3	100 ppm 550 mg/m3			
---	---------------------	----------------------	--	--	--

- UK :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
67-64-1 ACETONE	500 ppm 1210 mg/m3	1500 ppm 3620 mg/m3			
123-86-4 N-BUTYL ACETATE	150 ppm 724 mg/m3	200 ppm 966 mg/m3			
141-78-6 ETHYL ACETATE	200 ppm 734 mg/m3	400 ppm 1468 mg/m3			
13463-67-7 TITANIUM DIOXIDE [IN POWDER FORM CONTAINING 1 % OR MORE OF PARTICLES WITH AERODYNAMIC DIAMETER <= 10 µM]	4 mg/m3				
1330-20-7 XILENE (BENZENE <0.01%)	50 ppm 220 mg/m3	100 ppm 441 mg/m3			
108-65-6 2-METHOXY-1-METHYLETH YL ACETATE	50 ppm 274 mg/m3	100 ppm 548 mg/m3			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

2-METHOXY-1-METHYLETHYL ACETATE (CAS: 108-65-6)

Final use:

Exposure method:

Potential health effects:

DNEL :

Workers.

Dermal contact.

Long term local effects.

153 mg/kg body weight/day

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 9/23



Isseud by: SK	Confirmed by: GL
---------------	------------------

Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 275 mg of substance/m<sup>3</sup>

**Final use:**  
Exposure method: Ingestion.  
Potential health effects: Long term local effects.  
DNEL : 1,67 mg/kg body weight/day

Exposure method: Dermal contact.  
Potential health effects: Long term local effects.  
DNEL : 55 mg/kg body weight/day

Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 33 mg of substance/m<sup>3</sup>

## XILENE (BENZENE <0.01%) (CAS: 1330-20-7)

**Final use:**  
Exposure method: Inhalation.  
Potential health effects: Short term local effects.  
DNEL : 289 mg of substance/m<sup>3</sup>

Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 77 mg of substance/m<sup>3</sup>

**Final use:**  
Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 14.8 mg of substance/m<sup>3</sup>

## ETHYL ACETATE (CAS: 141-78-6)

**Final use:**  
Exposure method: Dermal contact.  
Potential health effects: Long term local effects.  
DNEL : 63 mg/kg body weight/day

Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 734 mg of substance/m<sup>3</sup>

Exposure method: Inhalation.  
Potential health effects: Short term local effects.  
DNEL : 1468 mg of substance/m<sup>3</sup>

**Final use:**  
Exposure method: Ingestion.  
Potential health effects: Long term local effects.  
DNEL : 4.5 mg/kg body weight/day

Exposure method: Dermal contact.  
Potential health effects: Long term local effects.  
DNEL : 37 mg/kg body weight/day

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 10/23



Isseud by: SK

Confirmed by: GL

Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 367 mg of substance/m3

Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 734 mg of substance/m3

## N-BUTYL ACETATE (CAS: 123-86-4)

**Final use:** Workers.  
Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 480 mg of substance/m3

Exposure method: Inhalation.  
Potential health effects: Short term systemic effects.  
DNEL : 960 mg of substance/m3

**Final use:** Consumers.  
Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 102 mg of substance/m3

## ACETONE (CAS: 67-64-1)

**Final use:** Workers.  
Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 1210 mg of substance/m3

Exposure method: Inhalation.  
Potential health effects: Short term local effects.  
DNEL : 2400 mg of substance/m3

**Final use:** Consumers.  
Exposure method: Dermal contact.  
Potential health effects: Long term local effects.  
DNEL : 62 mg/kg body weight/day

Exposure method: Dermal contact.  
Potential health effects: Long term local effects.  
DNEL : 186 mg/kg body weight/day

Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 200 mg of substance/m3

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 11/23



Isseud by: SK	Confirmed by: GL
---------------	------------------

## Predicted no effect concentration (PNEC):

### ETHYL ACETATE (CAS: 141-78-6)

Environmental compartment: PNEC :	Air. 0.2 mg/m <sup>3</sup>
Environmental compartment: PNEC :	Soil. 0.24 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.26 mg/l
Environmental compartment: PNEC :	Sea water. 0.026 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 1.65 mg/m <sup>3</sup>
Environmental compartment: PNEC :	Fresh water sediment. 1.25 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.125
Environmental compartment: PNEC :	Waste water treatment plant. 650 mg/l

### ACETONE (CAS: 67-64-1)

Environmental compartment: PNEC :	Soil. 33.3 mg/kg
Environmental compartment: PNEC :	Fresh water. 10.6 mg/l
Environmental compartment: PNEC :	Sea water. 1.06 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 21 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 30.4 mg/l
Environmental compartment: PNEC :	Marine sediment. 3.04 mg/l
Environmental compartment: PNEC :	Waste water treatment plant. 100 mg/l

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 12/23



Issued by: SK

Confirmed by: GL

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard ISO 16321.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

#### - Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149/A1.

Category :

- FFP1

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 13/23



Isseud by: SK

Confirmed by: GL

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Particle filter according to standard EN143 :

- P1 (White)

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### Physical state

Physical state : Viscous liquid.  
Spray.

Pressure container with product and liquefied gas

#### Colour

In accordance with the product designation

#### Odour

Odour threshold : Not stated.

Solvent

#### Melting point

Melting point/melting range : Not specified.

#### Freezing point

Freezing point / Freezing range : < 0 °C

#### Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not specified.

#### Flammability

Flammability (solid, gas) : < 0 °C

#### Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) 1,9 Vol % (LEL)

:

Explosive properties, upper explosivity limit (%) 15,0 Vol % (UEL)

:

#### Flash point

Flash point interval : Not relevant.

#### Auto-ignition temperature

Self-ignition temperature : Not specified.

#### Decomposition temperature

Decomposition point/decomposition range : Not specified.

#### pH

pH : Not stated.

Neutral.

pH (aqueous solution) : Not stated.

Not applicable due to the nature of the product.

#### Kinematic viscosity

Viscosity : Not stated.

#### Solubility

Water solubility : Insoluble.

Fat solubility : Not stated.

#### Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 14/23



Issued by: SK

Confirmed by: GL

## Vapour pressure

Vapour pressure (50°C) : Not relevant.  
4,0 +/- 0,2 Bar a 20C

## Density and/or relative density

Density : 0,72 +/- 0,01 g/cm<sup>3</sup> à 20 °C

## Relative vapour density

Vapour density : Not stated.

## Particle characteristics

The mixture does not contain nanoforms.

## 9.2. Other information

% VOC : >573 -<658 g/l

### 9.2.1. Information with regard to physical hazard classes

No data available.

#### Aerosols

Chemical combustion heat : Not specified.

Inflammation time : Not specified.

Deflagration density : Not specified.

Inflammation distance : Not specified.

Flame height : Not specified.

Flame duration : Not specified.

### 9.2.2. Other safety characteristics

No data available.

## SECTION 10 : STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating

- heat

### 10.5. Incompatible materials

Keep away from oxidant, strong acid and strong alkali, in order to avoid corrosion of steel containers

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 15/23



Isseud by: SK

Confirmed by: GL

## SECTION 11 : TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1. Substances

##### a) Acute toxicity :

HYDROCARBONS, C3-C4 (PROPANE, BUTANE, ISOBUTANE) (CAS: 68476-40-4)

Inhalation route (Dusts/mist) : LC50 = 1443 mg/m<sup>3</sup>  
Species : Rat

2-METHOXY-1-METHYLETHYL ACETATE (CAS: 108-65-6)

Oral route : LD50  $\geq$  5000 mg/kg body weight  
Species : Rat

Dermal route : LD50 > 5000 mg/kg body weight  
Species : Rat

Inhalation route (Dusts/mist) : LC50 = 37 mg/l  
Species : Rat  
Duration of exposure : 4 h

XILENE (BENZENE <0.01%) (CAS: 1330-20-7)

Oral route : LD50 = 5267 mg/kg body weight  
Species : Rat

Dermal route : LD50 > 5000 mg/kg body weight  
Species : Rabbit

Inhalation route (Dusts/mist) : LC50 = 20 mg/l  
Species : Rat

ETHYL ACETATE (CAS: 141-78-6)

Oral route : LD50 > 4934 mg/kg body weight  
Species : Rat

Dermal route : LD50 > 20000 mg/kg body weight  
Species : Rabbit

Inhalation route (Dusts/mist) : LC50 < 6000 ppm  
Species : Rat

N-BUTYL ACETATE (CAS: 123-86-4)

Oral route : LD50 > 6400 mg/kg body weight  
Species : Rat

Dermal route : LD50 > 5000 mg/kg body weight  
Species : Rabbit

Inhalation route (Dusts/mist) : LC50 = 21 mg/l  
Species : Rat

ACETONE (CAS: 67-64-1)

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 16/23



Issued by: SK

Confirmed by: GL

Oral route : LD50 = 5800 mg/kg body weight  
Species : Rat

Dermal route : LD50 > 7426 mg/kg body weight  
Species : Rat

Inhalation route (Vapours) : LC50 = 76 mg/l  
Species : Rabbit  
Duration of exposure : 4 h

**b) Skin corrosion/skin irritation :**

No data available.

**c) Serious damage to eyes/eye irritation :**

No data available.

**d) Respiratory or skin sensitisation :**

No data available.

**e) Germ cell mutagenicity :**

No data available.

**f) Carcinogenicity :**

No data available.

**g) Reproductive toxicant :**

No data available.

**h) Specific target organ systemic toxicity - single exposure :**

No data available.

**i) Specific target organ systemic toxicity - repeated exposure :**

No data available.

**j) Aspiration hazard :**

No data available.

## 11.1.2. Mixture

### 11.1.2.1 Information on hazard classes

**a) Acute toxicity :**

Oral route : No data available.

Dermal route : No data available.

Inhalation route (Dusts/mist) : No data available.

**b) Skin corrosion/skin irritation :**

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

**c) Serious damage to eyes/eye irritation :**

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.  
Splashes in the eyes may cause irritation and reversible damage

**d) Respiratory or skin sensitisation :**

No data available.

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 17/23



Issued by: SK

Confirmed by: GL

**e) Germ cell mutagenicity :**

No data available.

**f) Carcinogenicity :**

No data available.

**g) Reproductive toxicant :**

No data available.

**h) Specific target organ systemic toxicity - single exposure :**

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

**i) Specific target organ systemic toxicity - repeated exposure :**

No data available.

**j) Aspiration hazard :**

No data available.

### 11.1.2.2 Other information

#### Symptoms related to the physical, chemical and toxicological characteristics

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

#### Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 1330-20-7 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 13463-67-7 : IARC Group 2B : The agent is possibly carcinogenic to humans.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

## SECTION 12 : ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### 12.1.1. Substances

##### 2-METHOXY-1-METHYLETHYL ACETATE (CAS: 108-65-6)

Fish toxicity : LC50 = 180 mg/l  
Species : *Oncorhynchus mykiss*  
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 500 mg/l  
Species : *Daphnia magna*

Algae toxicity : ECr50  $\geq$  400 mg/l  
Duration of exposure : 48 h

##### XILENE (BENZENE <0.01%) (CAS: 1330-20-7)

Fish toxicity : LC50 = 2.6 mg/l  
Species : *Oncorhynchus mykiss*

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 18/23



Isseud by: SK

Confirmed by: GL

Crustacean toxicity :

EC50 = 1 mg/l  
Species : Daphnia magna  
Duration of exposure : 24 h

Algae toxicity :

ECr50 = 4.36 mg/l  
Species : Pseudokirchnerella subcapitata  
Duration of exposure : 72 h

ETHYL ACETATE (CAS: 141-78-6)

Fish toxicity :

LC50 > 230 mg/l

Species : Pimephales promelas  
Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 165 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

NOEC = 2.4 mg/l  
Species : Others  
Duration of exposure : 7 days

Algae toxicity :

ECr50 > 100 mg/l  
Species : Scenedesmus subspicatus  
Duration of exposure : 72 h

NOEC > 100 mg/l  
Species : Scenedesmus subspicatus  
Duration of exposure : 72 h

Aquatic plant toxicity :

NOEC > 1 mg/l

N-BUTYLACETATE (CAS: 123-86-4)

Fish toxicity :

LC50 = 18 mg/l  
Species : Pimephales promelas  
Duration of exposure : 96 h

Crustacean toxicity :

EC50 44 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

Algae toxicity :

Species : Pseudokirchnerella subcapitata

ACETONE (CAS: 67-64-1)

Fish toxicity :

LC50 = 302 mg/l  
Species : Others  
Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 4042 mg/l  
Species : Daphnia pulex  
Duration of exposure : 48 h

Algae toxicity :

ECr50 = 1680 mg/l  
Species : Others  
Duration of exposure : 48 h

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVKF(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 19/23



Isseud by: SK	Confirmed by: GL
---------------	------------------

HYDROCARBONS, C3-C4 (PROPANE, BUTANE, ISOBUTANE) (CAS: 68476-40-4)

Fish toxicity : LC50 = 24.11 mg/l  
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 14.22 mg/l  
Duration of exposure : 48 h

## 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

## 12.2. Persistence and degradability

### 12.2.1. Substances

2-METHOXY-1-METHYLETHYL ACETATE (CAS: 108-65-6)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

XILENE (BENZENE <0.01%) (CAS: 1330-20-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

ETHYL ACETATE (CAS: 141-78-6)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

N-BUTYL ACETATE (CAS: 123-86-4)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

ACETONE (CAS: 67-64-1)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

HYDROCARBONS, C3-C4 (PROPANE, BUTANE, ISOBUTANE) (CAS: 68476-40-4)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

## 12.3. Bioaccumulative potential

The propellant and the solvents have low split coefficients n-octanol/water and are not definable as bio accumulative. Not applicable

## 12.4. Mobility in soil

The propellant and the solvents are dispersed quickly in the air, without polluting of the soil. No data available on mobility in soil (due to missing data on substances not yet supplied by our suppliers)

## 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) 1907/2006 concerning the Registration, Evaluation, Restriction of chemicals substances (see section 3 and 2): does not meet the criteria for classification as PBT and vPvB therefore - not applicable. Use according to good working practices, avoiding to disperse the product into the environment.

## 12.6. Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with environmental effects.

## 12.7. Other adverse effects

The solvents and propellant contained have a low level of photochemical ozone creation potential.

N/A

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
 VVFK(E) : 01/1513231 -57, 1513260  
 Rev : B  
 Page : 20/23



Isseud by: SK	Confirmed by: GL
---------------	------------------

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

N/A

### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

## SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2025 - IMDG 2024 [42-24] - ICAO/IATA 2026 [67]).

### 14.1. UN number or ID number

1950

### 14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

### 14.3. Transport hazard class(es)

- Classification :



2.1

### 14.4. Packing group

-

- ADR, IMDG, IATA not required

### 14.5. Environmental hazards

- Marine pollutant : No

### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	-	-	Forbidden	Forbidden	203	150 kg	A1 A145 A167 A802	E0
	2.1	-	-	Forbidden	Forbidden	-	-	A1 A145 A167 A802	E0

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVFK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 21/23



Isseud by: SK

Confirmed by: GL

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.  
For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15 : REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Directive 2012/18/EU - Seveso III – Annex 1

P3a FLAMMABLE AEROSOLS (see note 11.1)

Category 1 "flammable" aerosols containing Category 1 flammable gases

#### Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 75/324/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2025/1222. (ATP 23)

#### Container information:

No data available.

#### Particular provisions :

No data available.

#### Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):  
<https://echa.europa.eu/substances-restricted-under-reach>.

#### Authorisations agreed under Title VII of Regulation (EC) No.1907/2006 (REACH):

The mixture does not contain any substance subject to authorisation according to Annex XIV of REACH Regulation (EC) No 1907/2006: <https://echa.europa.eu/fr/authorisation-list>.

#### Ozone-depleting substances (Regulation (EC) No 2024/590).

The mixture does not contain any substance posing a risk to the ozone layer.

#### Persistent organic pollutants (POP) (Regulation (EU) 2019/1021):

The mixture does not contain a persistent organic pollutant.

#### PIC Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (Rotterdam Convention):

The mixture is not subject to the Prior Informed Consent (PIC) procedure.

#### Explosives precursors :

The mixture contains at least one substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors:

- Acetone (CAS 67-64-1)

The acquisition, introduction, possession or use of this restricted explosive precursor by members of the general public is subject to the reporting obligations.

#### Swiss ordinance on the incentive tax on volatile organic compounds :

1330-20-7	xylenes (mixtures of isomers)
108-65-6	1-methoxy-2-propyl acetate (propylene glycol monomethyl ether acetate)
123-86-4	n-butyl acetate
141-78-6	ethyl acetate
67-64-1	acetone

### 15.2. Chemical safety assessment

The exposure scenarios of the substances leading to the classification of the mixture are available. A chemical safety assessment has not been carried out.

# Safety data sheets Ferney Group BV

Date : 27-03-2026  
VVK(E) : 01/1513231 -57, 1513260  
Rev : B  
Page : 22/23



Issued by: SK

Confirmed by: GL

## SECTION 16 : OTHER INFORMATION

### Wording of the phrases mentioned in section 3 :

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.  
LC50 : The concentration of a test substance resulting in 50% lethality in a given period.  
EC50 : The effective concentration of substance that causes 50% of the maximum response.  
ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.  
LQ : Limited Quantity  
EQ : Excepted Quantity  
EmS : Emergency Schedule  
E : Packing Instruction  
NOEC : The concentration with no observed effect.  
REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.  
ATE : Acute Toxicity Estimate  
BW : Body Weight  
DNEL : Derived No-Effect Level  
PNEC : Predicted No-Effect Concentration  
STEL : Short-term exposure limit  
TWA : Time-Weighted Average  
TMP : French Occupational Illness table  
VLE : Threshold Limit Value (exposure)  
VME : Average Exposure Value.  
VLRI : Indicative limit value  
VLRC : Indicative constraint value  
ADR : Agreement concerning the international carriage of dangerous goods by road.  
GHS02 : Flame

# **Safety data sheets Ferney Group BV**

**Date** : 27-03-2026  
**VVFK(E)** : 01/1513231 -57, 1513260  
**Rev** : B  
**Page** : 23/23



Isseud by: SK	Confirmed by: GL
---------------	------------------

---

GHS07 : Exclamation mark

IATA : International Air Transport Association.

IMDG : International Maritime Dangerous Goods.

ICAO : International Civil Aviation Organisation

PBT: Persistent, bioaccumulable and toxic.

PIC: Prior Informed Consent.

POP: Persistent Organic Pollutant.

RID : Regulations concerning the International carriage of Dangerous goods by rail.

SVHC : Substances of very high concern.

WGK : Water Hazard Class.

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.