

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





## EU Type Examination Certificate

Date: 2019/01/30 n. 158190506/OE

Validity: 2024/01/29

This Certificate cancels & replaces the previous one n° 158144501/OE dated 2014/11/06

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer:	GRISPORT SpA calzaturificio	
(Responsible of the PPE)	31030 CASTELCUCCO (TV) – Via Erega, 1 – ITALIA	
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in other materials)	n leather and
Category of PPE:	II: "medium" risks.  This certificate is based on reference standards listed below: its validity is ensured should new version of the standards come into force.	no l <mark>on</mark> ger
Model	"801LD21"	material code
Description:	design: A (= low shoe); fastening system: through laces; processing: direct injection; sole: black rubber marked "SAFETY VERA GOMMA MADE IN ITALY OIL RESISTANT ANTISTATIC HRO ABS ANTI SHOCK"; midsole + toe-tip outer reinforcement: foamed PU in "coffie" col.; upper: black leather art. "DAKAR TREKKING", declared thickness 2,0/2,2 with an insert "Support System" in the heel in black polymeric material; collar: black with white hatching fabric art. VANCOUVER 4017, matched to PE 40, with a grey insert in reflective mat. art. MOON LIGHT + ORLUX; tongue/bellows-tongue: black with white hatching fabric art. VANCOUVER 4017, centrally lined and padded; vamp lining: TNT (= non-woven) Aitelle 150 col. black, matched with MTP4 D40; guarter lining: TNT (= non-woven) Aitelle 150 col. black, matched with anthracite-grey rubber; insole: TNT (= non-woven mat.) art. STRONG IBITECH ANTISTATICO 252 in col. beige; penetration-resistant insert: inox steel art. 0785; removable insock: black perforated foamed material with aluminum oval insert stitched in the forepart with an antistatic zig-zag stitching, and an insert in boarskin nubuk in col."lontra" stitched in the heel area in contact with the foot:	022/ 1/00 2137BCP/00 - MPI/001 MPI/001 DAC/NER G016NG VAA/4017 MOX/47  VAN/4017 FCA/NEC FCA/NER ST2/GRI  SOTANT CIF/LON FLNPLCA
Technical Standard:	toe-cap: painted steel, reinforced and perforated, art. "SAFIT 604FR".  EN ISO 20344:2011 Personal protective equipment – Test method	604ACRF
rechnical Standard:	EN ISO 20344:2011  (UNI EN ISO 20345:2011  (UNI EN ISO 20345:2012)  Personal protective equipment – Test methods for footwear  Personal protective equipment – Safety footwear	
Intended use:	general industry, engineering industry, agriculture, warehouses, works on	trucks, cranes.
Size range:	from 39 to 48	
Technical File:	DC-9526/E + DC-6948/E	





1embro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC





## EU Type Examination Certificate

Date: 2019/01/30 n. 158190506/OE

Validity: 2024/01/29

Test report:

RCT n°334411.01

Functions and performance levels: basic requirements for safety footwear (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:

SRC (\*) = Slip resistance – meets the following requirement:

- <u>surface</u>: ceramic / <u>lubricant</u>: detergent solution;
- <u>surface</u>: steel / <u>lubricant</u>: glycerol.

Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011):

**S3 =** closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole; HI = heat insulation; HRO = resistance to hot contact of the outsole.

(\*) the final level of the anti-slip features is achieved after the first hours of trial stage.

Marking:

on a stitched label and containing the following information:

- CE Marking;
- name of the Manufacturer (printed on the heel and on the insole surface);
- designation of the footwear;
- Standard of reference + safety symbols;
- size of footwear (also printed in the outsole);
- month and year of production;
- additional info: internal code etc.







NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).