




MD092M4F430



Robert Bosch GmbH
 Postfach 41 09 60
 76225 Karlsruhe
 Auf der Breit 4
 76227 Karlsruhe-Durlach
 Tel 0721 942-0
 Fax 0721 942-2310
 www.bosch.com

Part Information				
Part No:	0 092 M4F 430			
Product Line:	M4			
Short Code:	M4F43			
Technology:	Flooded Lead Acid			
ETN:	519011019			
EAN-Code:	4047024510685			
Technical Information				
Nominal voltage:	12 V			
Nominal capacity: (20/5-hr discharge down to 10,5V)	C20 19 Ah	C5		
Reserve capacity: (@ 25A)				
Coldcranking Amps (EN / -18°C U _{10s} ≥ 7,5V)	240 A			
Boxsize:				
JIS-Code:	YB16L-B			
Permanent angle of inclination:	0°			
Short-term angle of inclination:	55°			
Maximum dimension	Length 176 mm	Width 101 mm	Height w/o Pol	Height w/ Pol 156 mm
Weight: (approx. filled battery)	6,11 kg			
Layout: (ETN, DIN 72 311)	1/2			
Terminal: (ETN, DIN 72 311)	Y6			
Degassing:	B			
Fastening: (ETN, DIN 72 311)	B00			
Execution:	-			
 				
Services				
Application:	Starter Battery			
Charging / discharging cycles:	-			
Service:	maintenance free			
Standard charging				
Charging voltage:	max. 14,4 V			
Charging current:	1,9A (10% nominal capacity in Amps)			
Charging pattern:	IU			
European standards:	DIN JIS 5302 Blei-Akkumulatoren –Starterbatterien; DIN 41 773, Ladegeräte mit IU-Kennlinie; DIN 43 530, Elektrolyt für Bleiakumulatoren			