DATASHEET



All-plastic cable ree Generation 7 Champion For permanent outdoor use.

 Article number:
 K750NTF101Z

 EAN:
 8715883032278

 Customs tariff number:
 8544429090

Country of origin: DE (non-preferential origin)




Manufacturer:

HEDI GmbH Elektro- und Gerätebau, Schöneggweg 17, D-87727 Babenhausen

Dimensions:

Total height: 415 mm
Reel housing diameter: 290 mm
Width (feet): 305 mm
Depth: 240 mm





Accessories

(included in delivery): twist grip cable guide

Spare parts: on request from the manufacturer

Carton (inner dimension LxWxH): 305 x 240 x 415 mm

Weight: 10.1 kg

Environmental / operating -25 ... +40°C

temperature:

DATASHEET



Material:

- Cable: neoprene-rubber (oil- and UV-resistend)

- Plug: rubber

- Feet: PA6GF30 + TPE (soft component in carrying and twist grip)

Reel housing: PP, redCable guide: PA6

- Socket insert: PP, sealing elements made of rubber

Electrical data:

- Operating voltage: 230 V ~ 50 Hz / 16 A

- Power rating: cable wound up 1,100 watts

cable unwound 3,500 watts 50 m H07RN-F 3G1.5 mm²

- Cable: 50 m H07RN-F 3G1.5 mm² - Plug: saftey plug 2p+E 16 A / 250 V

ı

- Socket: 4-fold safety socket German 16 A / 250 V / IP54

with thermal protection switch and diagnosis system DiagS:

- Green light on:

→ Cable reel ready for operating.

- Green + red light on:

→ Thermal protection switch has tripped.

→ Power supply has been interrupted.

- Protection class:

- Protection rating: IP54

- Area of application: For permanent outdoor use as well as on constructions

sites. Conforms tot he specifications of the DGUV-I 203-006 (formerly BGI 608) as well as of the DGUV I

203-005 (formerly BGI 600), K2.























