



All-plastic cable reel Generation 7 Champion For permanent outdoor use.

Article number: EAN: Customs tariff number: Country of origin:

K740N2TF101Z 8715883032292 8544429090 DE (non-preferential origin)



Manufacturer:

HEDI GmbH Elektro- und Gerätebau, Schöneggweg 17, D-87727 Babenhausen

Dimensions:

 Total height: Reel housing diameter: 	415 mm 290 mm
- Width (feet):	305 mm
- Depth:	240 mm



Accessories

(included in delivery):

twist grip cable guide

Spare parts:

on request from the manufacturer

Carton (inner dimension LxWxH): 305 x 240 x 415 mm

Weight:

11.8 kg

Environmental / operating -25 ... +40°C temperature:

DATASHEET



Material:

- Cable:
- Plug:
- Feet:
- Reel housing:
- Cable guide:
- Socket insert:

Electrical data:

- Operating voltage:
- Power rating:
- Cable:
- Plug:
- Socket:

neoprene-rubber (oil- and UV-resistend) rubber PA6GF30 + TPE (soft component in carrying and twist grip) PP, red PA6 PP, sealing elements made of rubber

230 V ~ 50 Hz / 16 A cable wound up 1,100 watts cable unwound 3,500 watts 40 m H07RN-F 3G2.5 mm² safety plug 2p+E 16 A / 250 V 4-fold safety socket German 16 A / 250 V / IP54 with thermal protection switch and diagnosis system DiagS: - Green light on: → Cable reel ready for operating. - Green + red light on:

- \rightarrow Thermal protection switch has tripped.
- \rightarrow Power supply has been interrupted.

- Protection class:
- Protection rating:
- Area of application:

IP54

L

For permanent outdoor use as well as on constructions sites. Conforms tot he specifications of the DGUV-I 203-006 (formerly BGI 608) as well as of the DGUV I 203-005 (formerly BGI 600), K2.



Status: 31.07.2024 Page 2 of 2