

Product specification

Date:2016-04-14 Index: 1



Product: G 165UN

Description: Precoated Glass textile wall covering for indoor walls and ceilings.

Composition: Texturized yarn of glassfiber in warp.
Sliveryarn of glassfiber in weft.
Precoated soft touch coating

Technical data:


| Properties | Unit | Min value | Nom value | Max value |
|-------------------------|--------------------|-----------|-----------|-----------|
| Width | mm | 990 | 1000 | 1010 |
| Length deviation | m | -0 | | |
| Thickness | mm | | 0,74 | |
| Total weight | g / m ² | 162 | 190 | 198 |
| Tensile strength | | | | |
| Warp direction | N / 5cm | 550 | 645 | |
| Weft direction | N / 5cm | 590 | 695 | |

Glue consumption Approx. 250 g / m². See also instructions on the glue bucket.

Paint consumption First coating Second coating
m² / litre 7,2

Facing side

Facing side is the outside of the roll.



Reverse side marking

Grey ink print 23 cm from the rolls edge.

Pattern matching

Offset match - thread to thread.



1,6cm



Pick over warpthread against pick under warpthread

Allowed amount of marked spot faults

Roll length 15m Max 1
Roll length 25 & 30m Max 2
Roll length 50m Max 3

Note: A joint can occur in a roll and is considered as a spot fault.

Certificates:



Storing: -10 to +50 degrees Celcius
Use within 2 years after production

Information above is accurate to the best of our knowledge. Our products are subject to rigorous quality control along the production line to ensure conformance. Divergence within our tolerance may occur.

Preiss-Daimler FibreGlass AB, Box 7013, S-250 07 Helsingborg. Tel +46 42 25 05 00, Fax + 46 42 16 01 42