

LED TL Luminaires with Tube - 2x20.5W 150cm 6200lm 4000K IP65 IK08



- ♦ 6200 Lumen
- ♦ Impact resistant and waterproof
- ♦ 150 Centimeter

This LED tube is a good lamp to illuminate large spaces. It has a brightness of 6200Lm. This fixture is suitable for damp rooms, such as basements and garages. The housing is made of polycarbonate that is very sturdy and can take a beating. This lamp is supplied with stainless steel mounting clips, 2 connections for wiring and a 2 20,5W LED tubes. This lamp is energy-efficient and environmentally friendly. These lamps are 150 cm long.

Article number LLW2400205_01

EAN 8718692548121

Brand



General

| | |
|-------------------------|------------|
| Warranty | 2-Year |
| Collection | Functional |
| Compliance certificates | CE |
| PLC Status | Active |

Lighting

| | |
|--|---------------|
| Photobiological safety according to EN 62471 | RG1 |
| Light color category | Neutral white |
| Color rendering index | 80 |
| Flicker-free | Yes |
| Beam angle | 120 ° |
| Equivalent light output | 116 W |
| Total lumens | 6200 lm |
| Color consistency (McAdam ellipse) | SDCM6 |
| Color temperature | 4000 K |
| Lamp efficacy | 151 |

Electrical

| | |
|-------------------|-----------------|
| Input current | 200 mA |
| Control gear type | Driver on board |

Performance

| | |
|---------------------------------|-------------|
| Operating temperature | -20 — 40 °C |
| Rated life time L80/B10 at 25 C | 25000 h |
| Impact strength | IK08 |
| Rated life time L70/B50 at 25 C | 50000 h |

| | |
|----------------------------|------|
| Energy class(EU 2019/2015) | D |
| Energy class(EU 874/2012) | A+ |
| IP Rating | IP65 |

Mechanical

| | |
|------------------------------|--------------------|
| Article width | 86 mm |
| Article height | 115 mm |
| With light source | No |
| Suitable for number of lamps | 2.00 |
| Color housing | White |
| Article length | 1500 mm |
| Housing material | Polycarbonate (PC) |
| Lamp socket | G13 |
| Di" user finishing | Transparent |

| | |
|---|--------------|
| Type of dimming | Not dimmable |
| Input frequency | 50/60 Hz |
| LED chip brand | Everlight |
| LED chip quantity | 216 |
| LED chip type | SMD 2835 |
| Nominal voltage | 220 — 240 V |
| Power consumption | 41.0 W |
| Voltage type | AC |
| Maximum qty per 16A type B circuit breaker | 60 |
| Glow wire test | 650 °C |

| | |
|--------------------|--------------------|
| Article net weight | 2600 g |
| Difuser material | Polycarbonate (PC) |

Logistic data

| | |
|--|---------------|
| CBM master carton | 0.10 m³ |
| Packaging height | 9.0 cm |
| Packaging width | 11.5 cm |
| Packaging length | 157.0 cm |
| HS Code | 9405920090 |
| Packaging gross weight | 2605.0 g |
| Packaging paper material weight | 78.0 g |
| EAN Product | 8718692548121 |
| Packaging plastic material weight | 17.00 g |
| HS Code_old | 9405920090 |
| Master carton quantity | 6 |
| Master carton width | 28 cm |
| Master carton length | 158 cm |
| Master carton height | 23 cm |
| Master carton gross weight | 16.54 kg |
| Master carton paper material weight | 1380.00 g |
| Master carton plastic material weight | 100.00 g |