

WhaleSpray

Technical Data Sheet

WS 3002 S

Family: 3
Product code: 3002S00



Creation date: 02/11/2010
Review date: 22/02/2018
Page: 1 / 2

Description

Oil degreaser.

Powerful engine surface cleaner / degreaser. Remove tar.

It is a mixture of solvents and emulsifiers of great strength for the removal of tar, oil and grease from all types of engines. The engine, once clean, runs more efficiently and without overheating. It is only necessary to spray on the surface of the motor, then rinse it and collect the remains of the rinse to give it the appropriate treatment.

Features and benefits

- Clean and degrease all types of motors.
- The emulsifying substances that make up this product make it possible to be easily removed with water. If necessary, collect the waste from the application to give it the appropriate treatment according to local waste treatment regulations.
- Easy to use with the spray gun type.
- Saves time for its fast-acting formulation.
- Leaves no undesirable odors in the engine compartment.
- Free of caustic substances.
- Safe to use due to its high flash point (> 70°C), even with a warm engine.
- The aerosol is equipped with a 360° pistol valve (spray in an inverted position) for easy application of the product. It is pressurized with non-flammable propellant, CO₂, providing a net product content of 97%.

Applications

- Automobile and truck engines.
- Boats.
- Lawn mowers.
- Agricultural machinery.
- Chainsaws.
- Workshop and construction equipment.



WhaleSpray
Spray everything

www.whalespray.com

P.I. Ametlla Park · c/ Aiguafreda, 24
08480 L'Ametlla del Vallès · Barcelona
Tel. 900 15 20 40

Síguenos en:



Empresa Certificada ISO 9001-ISO 14001
Company certified ISO 9001-ISO 14001

WhaleSpray

Technical Data Sheet

WS 3002 S

Family: 3
Product code: 3002S00



Creation date: 02/11/2010
Review date: 22/02/2018
Page: 2 de 2

How to use

Do not use with engines running.

Let the engine cool for 30 minutes before using the product.

Protect electrical, electronic parts and wiring from contact with the product and water.

Protect the ignition system (distributor and air intake) from contact with the product and water.

For good results, apply on dry and warm surfaces (do not use on hot surfaces).

Spray on the surface to be cleaned and leave to work for 10-15 minutes.

Remove with a strong jet of water or, if necessary, with a pressure washer.

Remove grease residues with a wire brush or spatula.

In case of difficulty in starting, apply **WS 1500 G / S** to displace the humidity.

Technical Data and Certificates

Appearance		Colorless liquid
Density	20 °C	0.82 g/cm ³
Flash point	Closed cup	72 °C
Distillation interval	Distillation	180-240 °C
Freeze point		<-30 °C
Jauri-Butanol value	Solvents	40
Non-volatile matter	12h 100°C	3.6%

FORMATS:
Aerosol



WhaleSpray
Spray everything

www.whalespray.com

P.I. Ametlla Park · c/ Aiguafreda, 24
08480 L'Ametlla del Vallès · Barcelona
Tel. 900 15 20 40

Síguenos en:



Empresa Certificada ISO 9001-ISO 14001
Company certified ISO 9001-ISO 14001