


Product specification

Date:2016-04-14 Index: 2



Installation steps



Product: G 116N

Description: Standard Glass textile wall covering for indoor walls and ceilings.

Composition: Yarn of glassfiber in warp.
Sliveryarn of glassfiber in weft.
Standard soft touch coating

Technical data:


Properties	Unit	Min value	Nom value	Max value
Width	mm	990	1000	1010
Length deviation	m	-0		
Thickness	mm		0,57	
Total weight	g / m ²	135	150	165
<u>Tensile strength</u>				
Warp direction	N / 5cm	469	552	
Weft direction	N / 5cm	639	799	

Glue consumption Approx. 250 g / m². See also instructions on the glue bucket.

<u>Paint consumption</u>	First coating	Second coating
m ² / litre	6,6	8,9

Facing side

Facing side is the outside of the roll.



Reverse side marking

Grey ink print 23 cm
from the rolls edge.

Pattern matching

Offset match - thread to thread.





Pick over warpthread against pick
under warpthread

Allowed amount of marked spot faults

Roll length 15m	Max 1
Roll length 25 & 30m	Max 2
Roll length 50m	Max 3

Note: A joint can occur in a roll and is considered as a spot fault.

Certificates:



Emissionsgeprüfte Wandbekleidung
nach DIN-Grundsitzen

Storing: -10 to +50 degrees Celcius
Use within 2 years after production

Information above is accurate to the best of our knowledge. Our products are subject to rigorous quality control along the production line to ensure conformance. Divergence within our tolerance may occur.

Preiss-Daimler FibreGlass AB, Box 7013, S-250 07 Helsingborg. Tel +46 42 25 05 00, Fax + 46 42 16 01 42