

Technical Data Sheet Ferney Group BV

Ferney Group BV
Ampèrestraat 15
1704 SM Heerhugowaard
Nederland

Date : 22-09-2025
TSFK : 25/1516434
Rev : A
Blad : 1/2



Productname: Kelfort® Wood Lubricant 400 ml

Prepared by: S.K.	Approved by: G.L.
-------------------	-------------------

The product:

The Kelfort® Wood Lubricant 400 ml is a high-quality, universal, silicone-free sliding and lubricating agent with many possible applications. It lubricates and reduces friction. The Kelfort® Wood Lubricant 400 ml does not stick or stain, thereby preventing the build-up of dirt, dust, or resin. Surfaces such as wood can be easily glued, painted, or stained after using this product.

Use:

- As a lubricant for woodworking machines.
- As a lubricant for spindles, gears, and guide rods.
- On sanding belts and sanding discs to prevent clogging, thereby extending the lifespan of the abrasive.
- As a sliding and lubricating agent for hinges, locks, sliding doors, windows, etc.

Properties:

- Durable
- Targeted spray pattern
- Silicone-free
- Multifunctional
- Lubricates, reduces friction, protects
- Does not stain
- Does not affect the substrate
- Extends the lifespan of abrasives and chisels

Application:

The surface must be clean, dry, and free of dust. Bring the spray can to room temperature (15–25 °C) and shake the Kelfort® Wood Lubricant 400 ml well before use. When spraying, keep a distance of approximately 25 cm from the surface to be treated.

If too much product has been applied, wipe off the excess with a clean cloth. Thanks to its silicone-free formulation, the Kelfort® Wood Lubricant 400 ml can be safely used on surfaces that will later be painted, glued, or printed. The materials on which it is applied will not be affected by the product.

Before use, carefully read and follow the instructions on the packaging.

Technical Data Sheet Ferney Group BV

Ferney Group BV
Ampèrestraat 15
1704 SM Heerhugowaard
Nederland

Date : 22-09-2025
TSFK : 25/1516434
Rev : A
Blad : 2/2



Productname: Kelfort® Wood Lubricant 400 ml

Technical Data:

<u>Odor:</u>	Specific
<u>Specific gravity (g/ml at 20°C):</u>	0,80 g/ml
<u>Base:</u>	Mineral oils
<u>Apperance:</u>	Clear, colorless oil
<u>Solubility:</u>	Insoluble in water
<u>Propellant:</u>	Propane-Butane
<u>VOC-CH %:</u>	75 %
<u>VOC-EU g/l:</u>	749 g/l
<u>Vapor presure at 20 ° C:</u>	3,7 – 4,3 bar
<u>Spray output:</u>	1,5 g/sec
<u>Storage:</u>	Store in a cool, dry place and protect from sunlight. Do not expose to temperatures above 50 °C.

Delivery form:

<u>Article number</u>	<u>Volume</u>	<u>EAN code</u>	<u>Color</u>	<u>Content of packaging</u>
1516434	400 ml	8714678243776	transparent	Pcs
1516434	400 ml	8714678243783	transparent	Box (12 pcs)
1516434	400 ml	8714678243790	transparent	Pallet (1008 pcs)

<u>Packaging:</u>	400 ml spray can
<u>Label information:</u>	Kelfort logo, article number, EAN code, description, and type
<u>Box content:</u>	12 pieces
<u>Dimensions spray can:</u>	(l x w x h): 6,6 x 6,6 x 20 cm
<u>Dimensions box:</u>	(l x w x h): 27 x 20,5 x 21 cm
<u>Dimensions pallet:</u>	(l x w x h): 120 x 80 x 120 cm
<u>Production information:</u>	The spray can displays a 7-digit production code: the first 2 digits before the slash (/) indicate the batch number, the first and fifth digits after the slash indicate the production year, and the middle 3 digits indicate the production day of the year. Example: 07/10654 07 = batch number 7 065 = 65th day of the year (in this case, March 6) 1...4 = production year (in this case, 2014)

<u>Shelf life:</u>	The wood lubricant has unlimited shelf life, provided it is stored according to the instructions.
--------------------	---