

### DESCRIPTION

The PSP 10-581 Allround Nitrile Foam Pro, 3/4 dipped is a glove with a 15G nylon liner covered with a 3/4 dipped breathable nitrile foam coating on the palm, fingers and partly the back. The back of the glove is partially open, which ensures good ventilation and therefore a fine wearing comfort. The open nitrile coating ensures a good grip on dry, wet and oily surfaces. This glove is also Food approved.

Article PSP 10-581 has been tested and certified in accordance with European Regulation (EU) 2016/425 and EN standards EN420 / EN388:2016.

### CHARACTERISTICS

- ▲ Nylon backing with lycra, 15 gauge
- ▲ 3/4 Dipped nitrile foam coating of top quality
- ▲ Tricot cuff
- ▲ Good grip in dry, wet and oily environments
- ▲ Breathable
- ▲ Food approved
- ▲ High wearing comfort
- ▲ Multifunctional use
- ▲ Excellent dexterity
- ▲ Excellent abrasion resistance
- ▲ Various sizes available
- ▲ Tests according to: EN420 / EN388:2016

### CERTIFICATIONS

  
CAT II

  
EN 388:2016  
4131X

Abrasion resistance = 4  
Cut resistance = 1  
Tear resistance = 3  
Puncture resistance = 1  
Cut ISO 13997 = X



### APPLICATIONS

Construction | Logistics | Industry | Logistics | Assembly |  
Installation | Precision work | Food industry + related services



### PRODUCT INFORMATION

|                    |                             |
|--------------------|-----------------------------|
| <b>Material</b>    | Liner: Nylon                |
|                    | Coating: Nitrile Foam       |
| <b>Color</b>       | Grey / Black                |
| <b>Length (mm)</b> | 230-270 Depends on the size |
| <b>Cuff</b>        | Elasticated knitted cuff    |

### ORDER DETAILS

| Size     | Item number    | Packing Units       |
|----------|----------------|---------------------|
| 07 / S   | 2.01.10.581.07 | 12 x 12 (144 pairs) |
| 08 / M   | 2.01.10.581.08 | 12 x 12 (144 pairs) |
| 09 / L   | 2.01.10.581.09 | 12 x 12 (144 pairs) |
| 10 / XL  | 2.01.10.581.10 | 12 x 12 (144 pairs) |
| 11 / XXL | 2.01.10.581.11 | 12 x 12 (144 pairs) |

Cut ISO 13997: The letter A to F indicates the cut resistance according to ISO 13997. X = Control not performed or not applicable

