

### WS 2400 S

Family: 2  
Product code: : 2400S85



Creation date: 02/11/2010  
Review date: 07/03/2018  
Page: 1 de 2

## Description

High performance grease + PTFE.

High purity, high quality white grease (NLGI Grade 2) with an advanced additive package including PTFE \* for superior lubrication. It has a smooth and creamy consistency for optimal surface coverage

## Features and benefits

- Provide long-lasting lubrication.
- Excellent resistance to water and heat.
- Contains corrosion inhibitors to ensure superior metal protection.
- Forms a strong, high-viscosity film.
- Suitable as a waterproof lubricant due to its water resistance properties.
- Reduces friction and wear in metal-metal and metal-plastic applications.
- It is sprayed like an oil, and remains like a grease.
- Suitable for vertical surfaces, does not drip or drip.
- White color allows easy visual inspection of film coverage.
- In the aerosol, hydrocarbons are used as a propellant to control the application and the thickness of the film.

## Application

### Long lasting lubrication

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Hinges</li> <li>• Gear and brake change mechanisms</li> <li>• Latches</li> <li>• Speedometer cables</li> <li>• Cables</li> <li>• Cam distributors</li> <li>• Lanes</li> </ul> | <ul style="list-style-type: none"> <li>• Seat guides</li> <li>• Open gears and chains</li> <li>• Water pumps</li> <li>• Sliding conveyors</li> <li>• Garage Door Guides</li> <li>• Rail guides</li> <li>• Motorcycle chains</li> </ul> |
|--|--|



### WS 2400 S

Family: 2  
Product code: 2400S85



Creation date: 02/11/2010  
Review date: 07/03/2018  
Page: 2 de 2

## How to use

- Shake well before use.
- Apply on dry and clean surfaces.
- Do not mix with other lubricants.
- Do not apply on connected equipment. Use in well ventilated areas.

## Technical data and certificates

Colour		White
Density, 15°C	SEB181301	900 Kg/m3
Penetration worked 0.1 mm	DIN ISO 2137	265-295
Consistency class	DIN 51818	NLGI 2
Drop point	DIN ISO 2176	260°C
Temperature range		-35 a +170°C
Estability at 100000 dH	DIN ISO 2137	<40
Estability at 2H shell-roller	DIN ISO 2137	<40
Water resistance	DIN 51807	0-90
Oxidation resistance 100H/99°C	DIN 51808	<0.3

FORMATS:  
Aerosol and bulk

