

WS 1422 S

Range 1
Product code: 1422S00



Creation Date 18/04/2018
Review Date;
Page: 1/2

DESCRIPTION

High performance cutting oil for extreme demands.

WS 1422 S is a special semi-synthetic lubricant, for metalworking applications, it is not miscible with water and is of direct use. Formulated with synthetic and natural bases.

High content of extreme pressure and anticorrosive additives. It presents a high polarity to metal surfaces.

Free of chlorine, suitable for all types of metals, except yellow metals.

CHARACTERISTICS AND ADVANTAGES

Extends the life of dies, punches and all kinds of tools.

Solves problems of grated, seizures...

Excellent anticorrosive power in the treated pieces.

Compatible with welding processes without prior degreasing.

Does not form lacquers or varnishes on the processed parts.

Excellent degreasing with aqueous alkaline systems if necessary.

Free of chlorine.

Formula with light controlled foam so it does not hang up vertically.

Provides an excellent finish on the treated surfaces.

APPLICATION

- Precision printing.
- Fine cut.
- Embodición of medium-high severity.
- Bending of stainless steel beams and hinges.
- Steels and steels of high alloy, as well as stainless steels.
- Punching, die cutting, threading, cutting.



WhaleSpray

Technical Data Sheet

WS 1422 S

Range 1
Product code: 1422S00



Creation date: 18/04/2018

Review date:

Page: 2/2

HOW TO USE

- Shake well before use.
- Apply with precision in the area to be treated.
- Use the cannula for high precision applications.
- If elimination is necessary, use WS 3015 S.

TECHNICAL DATA AND CERTIFICATES

Appearance		Transparent red
Flash point	ASTM D 92	>200°C
Welding charge (4 Balls test)	ASTM D 2783	>920 Kg
Cooper corrosion (3 h, 100°C)	ASTM D 130	2C

FORMATS:
Spray and bulk



WhaleSpray
Spray everything

www.whalespray.com

P.I. Ametlla Park · c/ Aiguafreda, 24
08480 L'Ametlla del Vallès · Barcelona
Tel. 900 15 20 40

Síguenos en:



Empresa Certificada ISO 9001-ISO 14001
Company certified ISO 9001-ISO 14001