

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVK(E) : 20/1526297
Rev : D
Page : 1/12



Isseud by: SK

Confirmed by: GL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Productname	Kelfort ® Marking paint fluor white
Article number	1526297
Producttype	Spray
Regulation	REACH (EG) regulation nr. 1907/2006 - nr. 2020/878
UFI- code	T970-C0C7-W000-985V

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Paint in aerosol form. For professional use only.
Uses advised against	All such use is not specified in this section, not in section 7.3.

1.3 Details of the supplier of the safety data sheet

Distributeur Ferney Group BV
Postbus 24
1700 AA Heerhugowaard – The Netherlands
T +31 (0)72-5765000 - F +31 (0)72-5765010
bedrijfsbureau@ferneygroup.nl - www.ferney.nl

1.4 Emergency telephone number

Noodtelefoon : +49(0)9366-907126 (ma-do 7.15-18.00 hour) or
: +31(0)88-7558000 (after worktime, exclusive use for doctors, pharmacists and government institutions)

Country	Organisation/ Company	Address	Emergency number	Comments
The Netherlands	National Poisons Information Center	House post number B.00.118 PO Box 85500 3508 GA Utrecht	+31 88 755 80 00	For the sole purpose of informing healthcare professionals in the event of acute poisoning

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Repeated exposure may cause skin dryness or cracking (EUH066).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

The propellant gas is not taken into account when determining the health and environmental classification of the mixture.

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVFK(E) : 20/1526297
Rev : D
Page : 2/12



Isseud by: SK

Confirmed by: GL

2.2. Label elements

The mixture is an aerosol fitted with a sealed spray attachment.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02

Signal Word :

DANGER

Hazard statements :

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Precautionary statements - Storage :

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Other information :

Do not use in a confined space.

Not to be used for any usage other than those specified.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 59 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	Classification (EC) 1272/2008	Note	%
INDEX: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32	GHS02, GHS04 Dgr Flam. Gas 1A, H220	C [i] [vii]	10 $\leq$ x % < 25
BUTANE CAS: 13463-67-7 EC: 236-675-5 REACH: 01-2119489379-17		[i]	2.5 $\leq$ x % < 10
TITANIUM DIOXIDE			

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVFK(E) : 20/1526297
Rev : D
Page : 3/12



Isseud by: SK

Confirmed by: GL

EC: 918-481-9 REACH: 01-2119457273-39 HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	GHS08 Dgr Asp. Tox. 1, H304 EUH066	P	2.5 <= x % < 10
EC: 927-241-2 REACH: 01-2119471843-32 HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLENES, < 2% AROMATICS	GHS08, GHS07, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066	P	2.5 <= x % < 10
INDEX: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4 REACH: 01-2119475103-46 ETHYL ACETATE	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[I]	2.5 <= x % < 10

Information on ingredients :

(Full text of H-phrases: see section 16)

[i] Substance for which maximum workplace exposure limits are available.

[vii] Propellant gas

Note P: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS 200-753-7).

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVFK(E) : 20/1526297
Rev : D
Page : 4/12



Isseud by: SK

Confirmed by: GL

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water
- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVFK(E) : 20/1526297
Rev : D
Page : 5/12



Issued by: SK

Confirmed by: GL

Fire prevention :

- Handle in well-ventilated areas.
- Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.
- Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.
- Do not spray on a naked flame or any incandescent material.
- Do not pierce or burn, even after use.
- Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.
- Keep packages tightly closed and away from sources of heat, sparks and naked flames.
- Do not use tools which may produce sparks. Do not smoke.
- Prevent access by unauthorised personnel.

Recommended equipment and procedures :

- For personal protection, see section 8.
- Observe precautions stated on label and also industrial safety regulations.
- Never pour water into this mixture.
- Do not breathe in aerosols.
- Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

- No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

- No data available.

Storage

- Keep out of reach of children.
- Keep the container tightly closed in a dry, well-ventilated place.
- Keep away from all sources of ignition - do not smoke.
- Keep well away from all sources of ignition, heat and direct sunlight.
- The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.
- Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

- Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

- No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
141-78-6 ETHYL ACETATE	734	200	1468	400	-

- UK :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8 BUTANE	600 ppm 1450 mg/m3	750 ppm 1810 mg/m3	-	-	-
13463-67-7 TITANIUM DIOXIDE	4 mg/m3	-	-	-	-
141-78-6 ETHYL ACETATE	200 ppm 734 mg/m3	400 ppm 1468 mg/m3	-	-	-

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVFK(E) : 20/1526297
Rev : D
Page : 6/12



Isseud by: SK

Confirmed by: GL

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard ISO 16321.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state :	Viscous liquid.
	Spray.

Colour

White

Odour

Odour threshold :	Not stated.
-------------------	-------------

Melting point

Melting point/melting range :	Not relevant.
-------------------------------	---------------

Freezing point

Freezing point / Freezing range :	Not stated.
-----------------------------------	-------------

Boiling point or initial boiling point and boiling range

Boiling point/boiling range :	Not relevant.
-------------------------------	---------------

Flammability

Flammability (solid, gas) :	Not stated.
-----------------------------	-------------

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) :	Not stated.
---	-------------

Explosive properties, upper explosivity limit (%) :	Not stated.
---	-------------

Flash point

Flash point interval :	Not relevant.
------------------------	---------------

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVFK(E) : 20/1526297
Rev : D
Page : 7/12



Issued by: SK

Confirmed by: GL

Auto-ignition temperature

Self-ignition temperature :	Not relevant.
-----------------------------	---------------

Decomposition temperature

Decomposition point/decomposition range :	Not relevant.
---	---------------

pH

pH (aqueous solution) :	Not stated.
-------------------------	-------------

pH :	Not relevant.
------	---------------

Kinematic viscosity

Viscosity :	Not stated.
-------------	-------------

Solubility

Water solubility :	Insoluble.
--------------------	------------

Fat solubility :	Not stated.
------------------	-------------

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water :	Not stated.
--	-------------

Vapour pressure

Vapour pressure (50°C) :	Not relevant.
--------------------------	---------------

Density and/or relative density

Density :	< 1
-----------	-----

Relative vapour density

Vapour density :	Not stated.
------------------	-------------

Particle characteristics

The mixture does not contain nanoforms.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

Aerosols

Chemical combustion heat :	Not specified.
----------------------------	----------------

Inflammation time :	Not specified.
---------------------	----------------

Deflagration density :	Not specified.
------------------------	----------------

Inflammation distance :	Not specified.
-------------------------	----------------

Flame height :	Not specified.
----------------	----------------

Flame duration :	Not specified.
------------------	----------------

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat
- humidity

Protect from moisture. Reaction with water can cause an exothermic reaction.

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVFK(E) : 20/1526297
Rev : D
Page : 8/12



Isseud by: SK

Confirmed by: GL

10.5. Incompatible materials

Keep away from :
- water

10.6. Hazardous decomposition products

The thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1. Substances

a) Acute toxicity :

HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLENES, < 2% AROMATICS

Oral route : LD50 > 5000 mg/kg body weight
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 5000 mg/kg body weight
Species : Rabbit
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Dusts/mist) : LC50 > 5000 mg/m³
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Oral route : LD50 > 5000 mg/kg body weight
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 2000 mg/kg body weight
Species : Rat
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Vapours) : LC50 5000

b) Skin corrosion/skin irritation :

No data available.

c) Serious damage to eyes/eye irritation :

No data available.

d) Respiratory or skin sensitisation :

No data available.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVFK(E) : 20/1526297
Rev : D
Page : 9/12



Issued by: SK

Confirmed by: GL

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2. Mixture

11.1.2.1 Information on hazard classes

a) Acute toxicity :

Oral route : No data available.

Dermal route : No data available.

Inhalation route (Dusts/mist) : No data available.

b) Skin corrosion/skin irritation :

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

c) Serious damage to eyes/eye irritation :

Splashes in the eyes may cause irritation and reversible damage

d) Respiratory or skin sensitisation :

No data available.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2.2 Other information

Symptoms related to the physical, chemical and toxicological characteristics

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

11.2. Information on other hazards

Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLENES, < 2% AROMATICS

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVFK(E) : 20/1526297
Rev : D
Page : 10/12



Isseud by: SK

Confirmed by: GL

TITANIUM DIOXIDE (CAS: 13463-67-7)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with environmental effects.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2025 - IMDG 2024 [42-24] - ICAO/IATA 2025 [66]).

14.1. UN number or ID number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification :



2.1

14.4. Packing group

-

14.5. Environmental hazards

-

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVFK(E) : 20/1526297
Rev : D
Page : 11/12



Issued by: SK

Confirmed by: GL

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	2	See SP63	-	See SP277	F-D, S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	Forbidden	Forbidden	203	150 kg	A1 A145 A167 A802	E0	
	2.1	-	-	Forbidden	Forbidden	-	-	A1 A145 A167 A802	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 75/324/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2024/2564. (ATP 22)

Container information:

No data available.

Particular provisions :

No data available.

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):

<https://echa.europa.eu/substances-restricted-under-reach>.

Authorisations agreed under Title VII of Regulation (EC) No.1907/2006 (REACH):

The mixture does not contain any substance subject to authorisation according to Annex XIV of REACH Regulation (EC) No 1907/2006:

<https://echa.europa.eu/fr/authorisation-list>.

Substances that deplete the ozone layer (EC Regulation No. 1005/2009, Montreal Protocol) :

The mixture does not contain any substance posing a risk to the ozone layer.

Persistent organic pollutants (POP) (Regulation (EU) 2019/1021):

The mixture does not contain a persistent organic pollutant.

PIC Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (Rotterdam Convention):

The mixture is not subject to the Prior Informed Consent (PIC) procedure.

Explosives precursors :

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

Swiss ordinance on the incentive tax on volatile organic compounds :

75-28-5	2-méthylpropane (alcool isobutylique, isobutane)
141-78-6	acétate d'éthyle
74-98-6	propane
106-97-8	n-butane

15.2. Chemical safety assessment

No data available.

Safety data sheets Ferney Group BV

Date : 15-10-2026
VVFK(E) : 20/1526297
Rev : D
Page : 12/12



Issued by: SK

Confirmed by: GL

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

LQ : Limited Quantity

EQ : Excepted Quantity

EmS : Emergency Schedule

E : Packing Instruction

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Moyenne pondérée dans le temps

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

GHS02 : Flame

IATA : International Air Transport Association.

IMDG : International Maritime Dangerous Goods.

ICAO : International Civil Aviation Organisation

PBT: Persistent, bioaccumulable and toxic.

PIC: Prior Informed Consent.

POP: Persistent Organic Pollutant.

RID : Regulations concerning the International carriage of Dangerous goods by rail.

SVHC : Substances of very high concern.

AK-erteke : Permissible average concentration

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.