



FLEXCORD PLUS COOLANT HOSE

Product Type:

Cooling Systems

Recommended for:

Light-duty automotive coolant applications. Designed to withstand severe conditions under the bonnet. This very flexible hose is also recommended for light-duty industrial applications. The hose absorbs vibrations and shocks and has a strong, supple body.

Resistant to:

Resistant to the harmful conditions under the bonnet; heat, ozone and coolant additives.

Construction:

Shape: Straight
Tube: EPDM
Reinforcement: Aramid
Wire: -
Cover: EPDM

Standards:

SAE Norm SAE 20R4 class D2
Din Norm DIN 73411 class B1

Temperature:

	PN								
		mm	"						
CH08100	4272-10080	8	5/16	12	1	135	4	16	3
CH10100	4272-10100	10	3/8	14	1	135	4	16	3
CH12100	4272-10120	12	1/2	16	1	135	4	16	3
CH15100	4272-10150	15	5/8	19	1	120	4	16	3
CH18100	4272-10180	18	11/16	22	1	120	4	16	3
CH20100	4272-10200	20	13/16	24	1	120	3	12	3
CH22100	4272-10220	22	7/8	26	1	90	3	12	3
CH25100	4272-10250	25	1	29	1	90	3	12	3
CH28100	4272-10280	28	1 1/8	32	1	90	3	12	3
CH30100	4272-10300	30	1 3/16	34	1	90	3	12	3
CH32100	4272-10320	32	1 1/4	36	1	90	3	12	3
CH35100	4272-10350	35	1 3/8	39	1	90	3	12	3
CH38100	4272-10380	38	1 1/2	43	1	60	3	12	3
CH40100	4272-10400	40	1 9/16	45	1	60	2	8.5	3
CH42100	4272-10420	42	1 5/8	47	1	60	2	8.5	3
CH45100	4272-10450	45	1 3/4	50	1	45	2	8.5	3
CH48100	4272-10480	48	1 7/8	53	1	45	2	8.5	3
CH50100	4272-10500	50	2	55	1	45	2	8.5	3