



# 05000DX1- Motor Oil 5W-20 Premium Synthetic DX1 FE Fuel Economy

Version du document: 30 aug. 2020



## Description

This MPM premium synthetic motor oil is specially formulated to meet the latest requirements for petrol engines of passenger cars, light commercial vehicles and SUVs. Particularly developed for the American and Asian markets. This fully synthetic engine oil offers total engine protection and keeps the engine clean even under the most severe conditions. Due to the good friction properties, MPG is enhanced. In addition, because of the excellent thin-flowability, this engine oil offers excellent cold start properties.

## Selon les spécifications de

API SN Plus / SN-RC  
Chrysler MS-6395  
Ford WSS-M2C945-A  
ILSAC GF-5  
Opel/GM dexos1™ Gen 2

## Unités d'emballage

ART. N°	VOLUME	ARTICLES PAR UNITÉ	ARTICLES PAR PALETTE
05001DX1-FE	1 L	6	450
05004DX1-FE	4 L	4	112
05005DX1-FE	5 L	4	112
05020DX1-FE	20 L	1	30
05060DX1-FE	60 L	1	12
05205DX1-FE	205 L	1	2
05999DX1-FE	1000 L	1	-
P05000DX1-FE	1 L	1	-

TEST	VALEUR	
Viscosity	5W-20	
SAE	5	
Density à 15 °Celsius	0.852	kg/l
Kinematic Viscosity à 40 °Celsius	48.9	mm <sup>2</sup> /s
Kinematic Viscosity à 100 °Celsius	8.72	mm <sup>2</sup> /s
Viscosity Index	158	
Flashpoint COC	228	°C
Pourpoint	-42	°C
Total Base Number	9.2	mgKOH/g
Sulphated Ash	0.88	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.