

**TECHNICAL DATASHEET****4tecx Spanhulzen blauw verzinkt**

Art.nr.	afmeting	Minimale besteleenheid	EAN-Code
4020200212	5.0 x 50mm	2000 stuks	8715883026253
4020200223	6.0 x 30mm	2000 stuks	8715883026260
4020200234	6.0 x 40mm	2000 stuks	8715883026277
4020200245	6.0 x 50mm	2000 stuks	8715883026284
4020200256	6.0 x 60mm	2000 stuks	8715883026291
4020200267	6.0 x 80mm	2000 stuks	8715883026307
4020200278	8.0 x 70mm	1000 stuks	8715883026314
4020200289	8.0 x 90mm	1000 stuks	8715883026321
4020200300	8.0 x 110mm	1000 stuks	8715883026338
4020200311	8.0 x 130mm	1000 stuks	8715883026345
4020200322	8.0 x 150mm	1000 stuks	8715883026352

Maat M5	Uittrekwaarde in beton - Kgf
5.0 x 50	80 kgf ~ hoger

Maat M6	Uittrekwaarde in beton - Kgf
6.0 x 30	100 kgf ~ hoger
6.0 x 40	120 kgf ~ hoger
6.0 x 50	140 kgf ~ hoger
6.0 x 60	140 kgf ~ hoger
6.0 x 80	140 kgf ~ hoger

Maat M8	Uittrekwaarde in beton - Kgf
8.0 x 50	200 kgf ~ hoger
8.0 x 70	200 kgf ~ hoger
8.0 x 90	200 kgf ~ hoger
8.0 x 110	200 kgf ~ hoger
8.0 x 130	200 kgf ~ hoger
8.0 x 150	200 kgf ~ hoger
8.0 x 180	200 kgf ~ hoger
8.0 x 200	200 kgf ~ hoger

Maat M5 : Inslag diepte in beton is 30mm  
 Maat M6 : Inslag diepte in beton is 30mm  
 Maar M6.0 x 30 – inslag diepte in beton is 27mm  
 Maat M8 : Inslag diepte in beton is 40mm

Standaard hardhead van de spanhulzen	
Maat M5, M6 & M8.0 x 90	HRC : 27 ~ 37
Maat M8	HRC : 25 ~ 35