



# 05000DX1 Motor Oil 5W-30 Premium Synthetic DX1

Version du document: 30 aug. 2020



## Description

This MPM premium synthetic motor oil is specially formulated to meet the latest requirements for petrol engines of passenger cars, light commercial vehicles and SUVs.

Developed for better low speed pre-ignition (LSPI) protection, particularly for Opel / GM small displacement turbo charged engines.

This fully synthetic engine oil offers total engine protection and keeps the engine clean even under the most severe conditions.

Due the excellent thin-flowability this engine oil offers excellent cold start properties.

## Selon les spécifications de

API SN Plus / SN-RC  
Chrysler MS-6395  
Ford WSS-M2C945-A / WSS-M2C946-A  
ILSAC GF-5  
Opel/GM dexos1™ Gen 2

## Unités d'emballage

ART. N°	VOLUME	ARTICLES PAR UNITÉ	ARTICLES PAR PALETTE
05001DX1	1 L	6	450
05005DX1	5 L	4	112
05020DX1	20 L	1	30
05060DX1	60 L	1	12
05205DX1	205 L	1	2
05999DX1	1000 L	1	-
P05000DX1	1 L	1	-

TEST	VALEUR	
Viscosity	5W-30	
SAE	5	
Density à 15 °Celsius	0.853	kg/l
Kinematic Viscosity à 40 °Celsius	60.9	mm <sup>2</sup> /s
Kinematic Viscosity à 100 °Celsius	10.4	mm <sup>2</sup> /s
Viscosity Index	159	
Flashpoint COC	221	°C
Pourpoint	-45	°C
Total Base Number	9.2	mgKOH/g
Sulphated Ash	0.94	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.