



Robert Bosch GmbH
 Postfach 41 09 60
 76225 Karlsruhe
 Auf der Breit 4
 76227 Karlsruhe-Durlach
 Tel 0721 942-0
 Fax 0721 942-2310
 www.bosch.com

| Part Information | |
|--|---|
| Bosch-PNo: | 0 092 S50 010 |
| Line Type: | S5 |
| Short Code: | S50 01 |
| ETN: | 552401052 |
| EAN-Code: | 4047023479426 |
| Technical Information | |
| Nominal voltage: | 12 V |
| Nominal capacity: (20-hr discharge down to 10,5V) | 52 Ah |
| Coldcranking Amps (EN / -18°C U10s ≥ 7,5V) | 520 A |
| Boxsize: | T4 |
| permanent angle of inclination: | 0° |
| short-term angle of inclination: | max. 90° |
| Maximum dimension | |
| Length: | 207 mm |
| Widths: | 175 mm |
| Height wa Pol: | 153 mm |
| Height w. Pol: | 175 mm |
| Weight: | approx. 12,73 kg |
| Layout: (ETN, DIN 72 311) | 0 |
| Terminal: (ETN, DIN 72 311) | 1 |
| Fastening: (ETN, DIN 72 311) | B13 |
| Services | |
| Application: | Starter battery |
| Service: | absolutely maintenance free |
| Standard charging | |
| Charging voltage: | max. 14,4 V |
| Charging current: | 6,0 A (10% nominal capacity in Amps) |
| Charging pattern: | IU |
| European Standards: | DIN EN 60095-1, -2, -4 Blei-Starterbatterien DIN EN 50342 Blei-Akkumulatoren –Starterbatterien DIN 41 773, Ladegeräte mit IU-Kennlinie DIN 43 530, Elektrolyt für Bleiakumulatoren |