

### WS 2250 S

Family: 2  
Product code: 2250S80



Creation date: 02/11/2010  
Review date 15/02/2018  
Page 1 / 1

## Description

Adhesive biodegradable grease with PTFE

Biodegradable, adhesive lubricant with white solid chain additives.

**WS 2250 S** is a highly adhesive spray lubricant for chains subject to high loads. It is characterized by a very good resistance to water and oxidation stability and can be used in corrosive and humid environments.

**WS 2250 S** is absolutely free of mineral oils. The synthetic ester used offers good temperature stability, up to 250°C., Also having emergency protection due to the presence of white solid lubricants

## Features and benefits

- Good penetrability and elasticity.
- Water resistant.
- Very adherent.
- Stable in the presence of acids.
- Low level of residue.
- Anti-wear properties.
- Prevents corrosion.
- High stability against loads, due to EP additives and solid lubricants.
- Excellent biodegradability thanks to the special oil used in its formulation.

## Applications

- For lubrication of transmission chains and conveyors of all kinds, for example: triple chains on work machines, forklift chains, mill chains and textile machines.
- For lubrication of motorcycle chains.
- For conservation of metallic cables, lubrication and maintenance.
- For lubrication of pinions and open gears in special cases.

## How to use

- Apply WS 2250 S on chains, sprockets or metal cables. After evaporation of the solvent, a resistant and highly adherent lubricating film remains.

FORMATS:  
Aerosol

