

Declaration of Performance (model in accordance with delegated regulation Nr. 574/2014 of the European Commission) Nr BRD004			
1.	Unique identification code of product-type	FOLIEFOL MULTITOP ST, Nr BRD004	
2.	Intended use/uses	Elastic sheets for the application of underlays for discontinuous roofing	
3.	Manufacturer	Berdal Rubber & Plastics BV Bedrijvenpark Twente 193 7602 KG Almelo – The Netherlands	
4.	Authorised representative	Not applicable	
5.	The system or systems for assessing and verifying performance resistance (AVCP)	AVCP 3	
6a.	Harmonised standard	EN 13859-1;2:2014	
	Notified authority	Centrum Stavebního inženýrství a.s., notification no.: 1390	
7.	Declared performance (s)	Essential features:	Performances:
		Fire reaction	Classe E
		Resistance to water ingress	Classe W1
		Tensile properties:	
		- Ultimate tensile strength:	250/165 (N/50 mm)
		- Maximum tensile strength after artificial ageing	220/145 (N/50 mm)
		Stretch	50/70 (%)
		Stretch after artificial ageing	40/60 (%)
		Tear resistance MD/CMD	115/135 (N)
Flexibility at low temperature	-30 °C		
<p>The performance of the product identified is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with (EU) No 305/2011, under the sole responsibility of manufacturer identified above.</p> <p>Signed for and on behalf of the manufacturer.</p> <p>B.M.D. van Kamperdijk, General Manager</p> <p>Almelo, The Netherlands, 1 March 2018</p>			