

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 1/19



Opgesteld door: DR

Bekrachtigd door: GL

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- 1.1 Product identifier

- Trade name: **Kelfort Brandwerend purschuim NB retourbus**

MSDS code:

- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

- **Application of the substance / the mixture** Sealant

- 1.3 Details of the supplier of the safety data sheet

- **Distributeur** Ferney Group BV Postbus 24
- 1700 AA Heerhugowaard - Nederland
- T +31 (0)72-5765000 - F +31 (0)72-5765010
- bedrijfsbureau@ferneygroup.nl - www.ferney.nl

- 1.4 Emergency telephone number:

- +49(0)9366-907126 (ma-do 7.15-18.00 uur) of
- +31(0)88-7558000 (na werktijd, uitsluitend voor artsen, apothekers en overheidsinstellingen)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)
GB

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 2/19



Opgesteld door: DR

Bekrachtigd door: GL

(Contd. of page 1)

- Hazard pictograms



GHS02 GHS07 GHS08

- Signal word Danger

- Contains:

diphenylmethanediisocyanate, isomers and homologues

- Hazard statements

- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P284 In case of inadequate ventilation wear respiratory protection.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- Supplemental information:

EUH204 Contains isocyanates. May produce an allergic reaction.
As from 24 August 2023 adequate training is required before industrial or professional use.
-feica.eu/PUinfo:



- 2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

- Determination of endocrine-disrupting properties

CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate

List II

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
 VVFK : 03/1516204
 Rev : H
 Blad : 3/19



Opgesteld door: DR

Bekrachtigd door: GL

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Active substance with propellant

· **Dangerous components:**

CAS: 9016-87-9 EC number: 618-498-9	diphenylmethanediisocyanate, isomers and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	30-<50%
CAS: 26040-51-7 EINECS: 247-426-5 Reg.nr.: 01-2119974586-20-xxxx	bis(2-ethylhexyl) tetrabromophthalate	10-<20%
CAS: 1244733-77-4 EC number: 807-935-0 Reg.nr.: 01-2119486772-26-xxxx	tris(2-chloro-1-methylethyl)phosphate Acute Tox. 4, H302; Aquatic Chronic 3, H412	10-<20%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<5%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<5%

· **EU SVHC** see Section 15

· **GB SVHC** see Section 15

· **Additional information:**

For the wording of the listed hazard phrases refer to section 16.

While curing the following substances are formed and released by a reaction with atmospheric humidity:

Carbon dioxide (CO₂)

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 4/19



Opgesteld door: DR

Bekrachtigd door: GL

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Take affected persons out of danger area and lay down.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If symptoms persist consult doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **Information for doctor:** No further relevant information available.
- **4.2 Most important symptoms and effects, both acute and delayed**
Irritating to eyes, respiratory system and skin.
May cause an allergic skin reaction.
Harmful if inhaled.
May cause damage to organs through prolonged or repeated exposure.
- **Hazards** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
- No further relevant information available.

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 5/19



Opgesteld door: DR

Bekrachtigd door: GL

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide (CO)
Carbon dioxide (CO₂)
Nitrogen oxides (NO_x)
Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen cyanide (HCN)
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Avoid contact with the eyes and skin.
Ensure adequate ventilation.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose of contaminated material as waste according to Section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Avoid contact with the eyes and skin.
Do not breathe vapour.
Wear suitable protective clothing and gloves.
Keep away from sources of ignition - No smoking.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
 VVFK : 03/1516204
 Rev : H
 Blad : 6/19



Opgesteld door: DR

Bekrachtigd door: GL

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

The usual precautionary measures are to be adhered to when handling chemicals.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility:

Store away from water.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Additional information about design of technical facilities: No further data; see item 7.

- Ingredients with limit values that require monitoring at the workplace:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

CAS: 115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

- PNECs

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

PNEC	1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water)
------	---

CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate

PNEC	0.64 mg/L (fresh water) 0.064 mg/L (marine)
PNEC	1.7 mg/kg dwt (soil) 1.34 mg/kg dwt (sediment (salt water))

CAS: 115-10-6 dimethyl ether

PNEC	0.155 mg/L (fresh water)
------	--------------------------

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 6/19



Opgesteld door: DR

Bekrachtigd door: GL

(Contd. of page 5)

PNEC	160 mg/L (sewage treatment plant)
	1.549 mg/L (intermittent release)
	0.016 mg/L (salt water)
	0.045 mg/kg (soil)
	0.069 mg/kg (sediment (salt water))

Ingredients with biological limit values:	
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues	
BMGV	1 µmol
	Sampling time: at the end of the period of exposure
	Parameter: isocyanate-derived diamine/mol creatinine in urine

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 7/19



Opgesteld door: DR	Bekrachtigd door: GL
--------------------	----------------------

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

- Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6.)

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 8/19



Opgesteld door: DR	Bekrachtigd door: GL
--------------------	----------------------

(Contd. of page 6)

· Eye protection:

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 8/19



Opgesteld door: DR

Bekrachtigd door: GL



Tightly sealed goggles

· **Body protection:**



Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not applicable, as aerosol. Undetermined.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	3.0 Vol %
· Upper:	18.6 Vol %
· Flash point:	-97 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Insoluble.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	>0 hPa
· Density and/or relative density	
· Density at 20 °C:	1.07 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 9/19



Opgesteld door: DR

Bekrachtigd door: GL

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EU) 183.1 g/l

· VOC (EC) 17.12 %

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void

· Flammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container: May burst if heated.

· Oxidising gases Void

· Gases under pressure Void

· Flammable liquids Void

· Flammable solids Void

· Self-reactive substances and mixtures Void

· Pyrophoric liquids Void

· Pyrophoric solids Void

· Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in contact with water Void

· Oxidising liquids Void

· Oxidising solids Void

· Organic peroxides Void

· Corrosive to metals Void

· Desensitised explosives Void

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 10/19



Opgesteld door: DR

Bekrachtigd door: GL

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Flammable.
Danger of bursting.

- **10.4 Conditions to avoid**
Water / moisture.
Keep away from heat, hot surfaces, sparks, open flames and other ignition source
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxide
Nitrogen oxides (NOx)
Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen cyanide (prussic acid)

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 11/19



Opgesteld door: DR	Bekrachtigd door: GL
--------------------	----------------------

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 12/19



Opgesteld door: DR

Bekrachtigd door: GL

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

Oral	LD50	>10,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	1.5 mg/L (rat)

CAS: 26040-51-7 bis(2-ethylhexyl) tetrabromophthalate

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,090 mg/kg (rabbit) (OECD 402)

CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate

Oral	LD50	>500 mg/kg (rat)
------	------	------------------

CAS: 115-10-6 dimethyl ether

Inhalative	LC50/4 h	308 mg/L (rat)
------------	----------	----------------

CAS: 74-98-6 propane

Inhalative	LC50/4 h	260,000 ppmV (rat)
	LC50/4 h	658 mg/m ³ (rat)

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity

Suspected of causing cancer.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 1244733-77-4 | tris(2-chloro-1-methylethyl)phosphate

List II

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 13/19



Opgesteld door: DR

Bekrachtigd door: GL

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

LC0/96 h >1,000 mg/L (brachydanio rerio)

EC50/24 h >1,000 mg/L (daphnia magna)

CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate

LC50/96 h 51 mg/L (pimephales promelas)

EC50/48 h 131 mg/L (daphnia magna)

EC50/96 h 131 mg/L (daphnia magna)

· **12.2 Persistence and degradability** No further relevant information available.

· **Other information:** The product is not easily biodegradable.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Ecotoxicological effects:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

NOEC/21 d >10 mg/L (daphnia magna)

· Other information:

This product contains no substances in Annex I to Directive EC 1005/2009 concerning ozone depleting substances

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 14/19



Opgesteld door: DR

Bekrachtigd door: GL

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Cured product can be deposited together with domestic waste. Observe the specific related regulations of local authorities.

This material and its container must be disposed of as hazardous waste.

Do not allow product to reach sewage system or any water course.

Do not pierce or burn, even after use.

- European waste catalogue

16 05 04*	gases in pressure containers (including halons) containing hazardous substances
08 05 01*	waste isocyanates
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP13	Sensitising

- Uncleaned packaging:

- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Dispose of packaging according to regulations on the disposal of packagings.

Veiligheidsvoorschriften Ferney Group BV



Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 15/19



Opgesteld door: DR

Bekrachtigd door: GL

SECTION 14: Transport information

<ul style="list-style-type: none">- 14.1 UN-Number- ADR, IMDG, IATA	UN1950
<ul style="list-style-type: none">- 14.2 UN proper shipping name- ADR- IMDG- IATA	1950 AEROSOLS 1950 AEROSOLS AEROSOLS AEROSOLS, flammable
<ul style="list-style-type: none">- 14.3 Transport hazard class(es)- ADR 	<ul style="list-style-type: none">- Class- Label 2 5F Gases. 2.1
<ul style="list-style-type: none">- IMDG, IATA 	<ul style="list-style-type: none">- Class- Label 2.1 2.1
<ul style="list-style-type: none">- 14.4 Packing group- ADR, IMDG, IATA	Void
<ul style="list-style-type: none">- 14.5 Environmental hazards:- Marine pollutant:	No
<ul style="list-style-type: none">- 14.6 Special precautions for user- Hazard identification number (Kemler code):- EMS Number:- Stowage Code - Segregation Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 16/19



Opgesteld door: DR

Bekrachtigd door: GL

-	For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
- Transport/Additional information:	
- ADR	
- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
- Transport category	2
- Tunnel restriction code	D
- IMDG	
- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
- UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 17/19



Opgesteld door: DR

Bekrachtigd door: GL

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
HSE EH40/2005 Workplace Exposure Limits (as amended)
Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015)
"GB- CLP" UK SI 2019 No. 720 The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019
"UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019
The Endocrine Disruptor Lists I, II, III (www.edlists.org)

- **Directive 2012/18/EU**

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 56a, 74

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **National regulations:**

- **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- **Other regulations, limitations and prohibitive regulations** No further relevant information available.

- **Substances of very high concern (SVHC) according to EU REACH, Article 57**

CAS: 26040-51-7 | bis(2-ethylhexyl) tetrabromophthalate

- **Substances of very high concern (SVHC) according to UK REACH** Not applicable.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 18/19



Opgesteld door: DR	Bekrachtigd door: GL
--------------------	----------------------

Veiligheidsvoorschriften Ferney Group BV

Datum : 19-04-2024
VVFK : 03/1516204
Rev : H
Blad : 19/19



Opgesteld door: DR

Bekrachtigd door: GL

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH204 Contains isocyanates. May produce an allergic reaction.

Department issuing SDS:

Prepared and verified in accordance with Annex II, Part A, 0.2.3. of "UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

Date of previous version: 24.08.2021

Version number of previous version: 10

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**