




M0092M4F390



Robert Bosch GmbH
 Postfach 41 09 60
 76225 Karlsruhe
 Auf der Breit 4
 76227 Karlsruhe-Durlach
 Tel 0721 942-0
 Fax 0721 942-2310
 www.bosch.com

Part Information				
Part No:	0 092 M4F 390			
Product Line:	M4			
Short Code:	M4F39			
Technology:	Flooded Lead Acid			
ETN:	516015016			
EAN-Code:	4047024510609			
Technical Information				
Nominal voltage:	12 V			
Nominal capacity: (20/5-hr discharge down to 10,5V)	C20 16 Ah	C5		
Reserve capacity: (@ 25A)				
Coldcranking Amps (EN / -18°C U _{10s} ≥ 7,5V)	200 A			
Boxsize:				
JIS-Code:	YB16B-A; YB16B-A1			
Permanent angle of inclination:	0°			
Short-term angle of inclination:	55°			
Maximum dimension	Length 160 mm	Width 90 mm	Height w/o Pol	Height w/ Pol 161 mm
Weight: (approx. filled battery)	5,17 kg			
Layout: (ETN, DIN 72 311)	2/1			
Terminal: (ETN, DIN 72 311)	Y4			
Degassing:	A			
Fastening: (ETN, DIN 72 311)	B00			
Execution:	-			
				
Services				
Application:	Starter Battery			
Charging / discharging cycles:	-			
Service:	maintenance free			
Standard charging				
Charging voltage:	max. 14,4 V			
Charging current:	1,6A (10% nominal capacity in Amps)			
Charging pattern:	IU			
European standards:	DIN JIS 5302 Blei-Akkumulatoren –Starterbatterien; DIN 41 773, Ladegeräte mit IU-Kennlinie; DIN 43 530, Elektrolyt für Bleiakumulatoren			