

## WS 1330 S/16

Family: 1  
Product code: 1330S16



Creation date: 02/11/2010  
Review date: 03/04/2018  
Page: 1 de 1

### DESCRIPTION

100% synthetic lubricating oil for high temperatures

Synthetic spray lubricant for chains and lubrication points at high temperatures. **WS 1330 S/16** is a high viscosity lubricating oil for chains, open gears. It offers excellent stability at low and high temperatures and guarantees very good protection against wear and corrosion.

**WS 1330 S/16** is also qualified for small chains. Penetrates and lubricates in small gaps and bolts and offers a long and durable film to prevent wear and good corrosion protection.

### CHARACTERISTICS AND ADVANTAGES

- Extreme stability to temperature.
- Excellent wear protection. Good properties at high loads.
- Low evaporation at high temperatures.
- Appropriate oxidation stability.
- Good sliding characteristics, penetrates between the spaces of the chains.
- Penetrates into links and offers excellent wear protection.
- Exceptional lubrication and spacer effect.
- Reduces the coefficient of friction to a minimum.
- Protects against corrosion and friction.
- High viscosity index, stable to temperature changes.

### APLICACIONES

- As a chain lubricant of all kinds, for example: in pasteurization plants, drying ovens, lacquering ovens, the textile industry, and other assembly lines and packaging equipment.
- For truck chains. For conveyor chains. Open gears.

### TECHNICAL DATA

Appearance		Brown synthetic oil
Density	DIN 51 757	0.95 g/cm <sup>3</sup>
Viscosity 40°C	DIN 51562	680 mm <sup>2</sup> /s
Viscosity 100°C	DIN 51562	150 mm <sup>2</sup> /s
Viscosity index	ISO 2909	125 ISO
Freezing point		-35°C
Temperature range		-30 to 300°C

FORMATS:  
Spray

