

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 1/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Productname	Kelfort ® purschuim SU-PUR NBS pistool 540ml
Article number	1516208
Producttype	Sealant
According Regulation (EC)	Acc. To (EC) No 1907/2006, as amended by UK SI 2019/758
UFI	WVN2-608R-T00P-1EP7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Sealant
-----------------	---------

1.3 Details of the supplier of the safety data sheet

Distributeur Ferney Group BV
Postbus 24
1700 AA Heerhugowaard – The Netherlands
T +31 (0)72-5765000 - F +31 (0)72-5765010
bedrijfsbureau@ferneygroup.nl - www.ferney.nl

1.4 Emergency telephone number

Noodtelefoon : +49(0)9366-907126 (ma-do 7.15-18.00 hour) or
: +31(0)30-2748888 (after worktime, exclusive use for doctors, pharmacists and government institutions)

Country	Organisation/ Company	Address	Emergency number	Comments
The Netherlands	National Poisons Information Center	House post number B.00.118 PO Box 85500 3508 GA Utrecht	+31 88 755 80 00	For the sole purpose of informing healthcare professionals in the event of acute poisoning

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 2/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Contains:

diphenylmethanediisocyanate, isomers and homologues

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P284 In case of inadequate ventilation wear respiratory protection.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Supplemental information:

EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 3/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· **Description:** Active substance with propellant

· **Dangerous components:**

CAS: 9016-87-9 EC number: 618-498-9	diphenylmethanediisocyanate, isomers and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	30-<50%
CAS: 1244733-77-4 EC number: 807-935-0 Reg.nr.: 01-2119486772-26-xxxx	tris(2-chloro-1-methylethyl)phosphate Acute Tox. 4, H302	10-<20%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 9082-00-2	Ethoxylated/propoxylated glycerol Acute Tox. 4, H302	5-<10%
CAS: 25791-96-2 NLP: 500-044-5	Glycerol, propoxylated Acute Tox. 4, H302	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<5%

· **SVHC -**

· **Additional information:**

For the wording of the listed hazard phrases refer to section 16.

While curing the following substances are formed and released by a reaction with atmospheric humidity:
Carbon dioxide (CO₂)

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 4/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

SECTION 4: First aid measures

4.1 Description of first aid measures

- **General information:** Take affected persons out of danger area and lay down.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately remove all soiled and contaminated clothing
If symptoms persist consult doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **Information for doctor:** No further relevant information available.

4.2 Most important symptoms and effects, both acute and delayed

- Harmful if inhaled.
- Irritating to eyes, respiratory system and skin.
- May cause an allergic skin reaction.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Suspected of causing cancer.
- May cause damage to organs through prolonged or repeated exposure.
- **Hazards** No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 5/17



Opgesteld door: SB

Bekrachtigd door: GL

SECTION 5: Firefighting measures

5.1 Extinguishing media

- **Suitable extinguishing agents:**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

Carbon dioxide (CO2)

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (HCN)

5.3. Advice for firefighters

- **Protective equipment:** Wear self-contained respiratory protective device.

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 6/17



Opgesteld door: SB

Bekrachtigd door: GL

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with the eyes and skin.

Ensure adequate ventilation.

6.2 Environmental precautions

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 7/17



Opgesteld door: SB

Bekrachtigd door: GL

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Avoid contact with the eyes and skin.

Avoid breathing vapours/spray.

Wear suitable protective clothing and gloves.

The usual precautionary measures are to be adhered to when handling chemicals.

· Information about fire - and explosion protection:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Do not spray onto a naked flame or any incandescent material.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Store away from water.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Do not seal receptacle gas tight.

Protect from heat and direct sunlight.

7.3 Specific end use(s)

No further relevant information available.

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 8/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

CAS: 115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

· PNECs

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

PNEC	1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water)
------	---

CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate

PNEC	0.64 mg/L (fresh water) 0.064 mg/L (marine)
PNEC	1.7 mg/kg dwt (soil) 1.34 mg/kg dwt (sediment (salt water))

CAS: 115-10-6 dimethyl ether

PNEC	0.155 mg/L (fresh water) 160 mg/L (sewage treatment plant) 1.549 mg/L (intermittent release) 0.016 mg/L (salt water)
PNEC	0.045 mg/kg (soil) 0.069 mg/kg (sediment (salt water))

· Additional Occupational Exposure Limit Values for possible hazards during processing:

While curing the following substances are formed and released by a reaction with atmospheric humidity:
Carbon dioxide (CO₂)

· Additional information: The lists valid during the making were used as basis.

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 9/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Ensure that washing facilities are available at the work place.

Avoid contact with the eyes and skin.

Avoid breathing dust/fume/gas/mist/vapours/spray.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

· Protection of hands:



Protective gloves

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

· Eye protection:



Tightly sealed goggles

· Body protection:



Protective work clothing

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 10/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

SECTION 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information	
· Appearance:	
Form:	Aerosol
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Mixture reacts violently with water.
· Melting point/freezing point:	Not applicable, as aerosol. Undetermined.
· Flash point:	-97 °C
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.8 Vol %
Upper:	18.6 Vol %
· Vapour pressure at 20 °C:	5,200 hPa
· Density at 20 °C:	0.98 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Immiscible / difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC (EU)	208.7 g/l
VOC (EC)	21.29 %

9.2 Other information

No further relevant information available.

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 11/17



Opgesteld door: SB

Bekrachtigd door: GL

Rubriek 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decompositions products

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (prussic acid)

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 12/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

SECTION 11: Toxicological information

11.1 Information on toxicological effects

· Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

Oral	LD50	>10,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	1.5 mg/L (rat)

CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate

Oral	LD50	632 mg/kg (rat)
------	------	-----------------

CAS: 9082-00-2 Ethoxylated/propoxylated glycerol

Oral	LD50	>500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

CAS: 25791-96-2 Glycerol, propoxylated

Oral	LD50	1,999 mg/kg (rat)
------	------	-------------------

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

· Additional toxicological information:

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity

Suspected of causing cancer.

· Reproductive toxicity

Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard

Based on available data, the classification criteria are not met.

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 13/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

SECTION 12: Ecological information

12.1 Toxicity

· Aquatic toxicity:	
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues	
LC0/96 h	>1,000 mg/L (brachydanio rerio)
EC50/24 h	>1,000 mg/L (daphnia magna)
CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate	
LC50/96 h	51 mg/L (pimephales promelas)
CAS: 9082-00-2 Ethoxylated/propoxylated glycerol	
LC50/48 h	>100 mg/L (brachydanio rerio)
EC50/48 h	>100 mg/L (daphnia magna)
EC50/72 h	>1,000 mg/L (scenedesmus capricornutum)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

· Ecotoxicological effects:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues	
NOEC/21 d	>10 mg/L (daphnia magna)

· Other information:

This product contains no substances in Annex I to Directive EC 1005/2009 concerning ozone depleting substances

12.5 Result of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

12.6 Other adverse effects

No further relevant information available.

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 14/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

SECTION 13: Disposal considerations

13.1 Waste treatment methods

· Recommendation

Disposal must be made according to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Do not pierce or burn, even after use.

· European waste catalogue

16 05 04*	gases in pressure containers (including halons) containing hazardous substances
08 05 01*	waste isocyanates
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP13	Sensitising

· Uncleaned packaging:

· Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

SECTION 14: Transport information

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
· ADR	1950 AEROSOLS
	1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 15/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
	
· Class	2.1
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Segregation Code	
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 16/17



Opgesteld door: SB	Bekrachtigd door: GL
--------------------	----------------------

· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15 Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

"EU-CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1)

"EU-REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments)
COMMISSION REGULATION (EU) 2020/878 of 18 June 2020.

75/324/EEC relating to aerosol dispensers

HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015)

"GB-CLP" The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use)
(Amendment etc.) (EU Exit) Regulations 2019

"UK-REACH" The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

· Directive 2012/18/EU

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Other regulations, limitations and prohibitive regulations No further relevant information available.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

Safety data sheets Ferney Group BV

Date : 22-03-2024
VVFK : 04/1516208
Rev : H
Page : 17/17



Opgesteld door: SB

Bekrachtigd door: GL

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Department issuing SDS:

Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
*** Data compared to the previous version altered.**

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.