

DESCRIPTION

The PSP Cut Protect, Cut D PU Grey 15-600 is a glove with a 13 gauge HDPE/Polyester + fiber reinforced liner with cut resistant protection and PU palm.


The back is open, which provides good ventilation and as a result an excellent comfort. The open PU coating provides a good grip on dry and oily environments.

This article (PSP Cut D PU Grey 15-600) has been tested and is certified according to the requirements of Regulation (EU) 2016/425 and European standards EN 420: 2003 + A1: 2009 and EN 388:2016.


CHARACTERISTICS

- ▲ Cut resistance according to ISO 13997: result D
- ▲ HDPE/Polyester + fiber reinforced liner, 13 gauge
- ▲ PU coating
- ▲ Elasticated knitted cuff
- ▲ Good grip in dry and oily environments
- ▲ Breathable
- ▲ Excellent comfort
- ▲ Good finger dexterity
- ▲ High abrasion and tear resistance
- ▲ Multifunctional
- ▲ Available in various sizes
- ▲ Certification according to: EN420 / EN388:2016

CERTIFICATIONS


 CAT II

EN 388:2016


 4X42D

Abrasion resistance = 4
 Blade cut resistance = X
 Tear resistance = 4
 Puncture resistance = 2
 Cut ISO 13997 = D



PROPERTIES

Construction | Logistics | Industry | Construction | Transport | Assembly | Installation



PRODUCT INFORMATION

Material	Liner: HDPE/Polyester + fiberglass Coating: Polyurethane
Color	Grey / Grey
Length (mm)	220-260 Depending on the size
Cuff	Elastic knitted wrist

ORDER DETAILS

Size	Item number	Packing Unit
07 / S	2.01.15.600.07	12 x 12 (144 pairs)
08 / M	2.01.15.600.08	12 x 12 (144 pairs)
09 / L	2.01.15.600.09	12 x 12 (144 pairs)
10 / XL	2.01.15.600.10	12 x 12 (144 pairs)
11 / XXL	2.01.15.600.11	12 x 12 (144 pairs)
12 / 3XL	2.01.15.600.12	12 x 12 (144 pairs)

Cut ISO 13997: The letter A to F indicates the cut resistance according to ISO 13997. X = control not performed or not applicable

