

Bedrijvenpark Twente 193 NL-702 KG Almelo – The Netherlands

Tel: +31 (0)546 - 572 672 Mail: info@berdal.com

		claration of Performance gated regulation Nr. 574/2014 of the nr BRD006	e European Commission)
1.	Unique identification code of product-type	FOLIEFOL TOP G Alu, nr BRD006	
2.	Intended use/uses	Reinforced elastic sheets for the application of underlayer for discontinuous roofing	
3.	Manufacturer	Berdal Rubber & Plastics BV Bedrijvenpark Twente 193 7602 KG Almelo – The Netherlands	
4.	Authorised representative	Not applicable	
5.	The system or systems for assesssing and verifying performance resistance (AVCP)	AVCP 3	
6a.	Harmonised standard	EN 13859-1	
	Notified authority	Centrum Stavebniho inzenyrstvi a.s., notification no.: 1390	
7.	Declared performance (s)	Essential features:	Performances:
		Fire reaction	Classe E
		Impermeability	Classe W1
		Water vapour transmission rate (Sd)	600 m
	*	Impact load resistance	NPD (no performance determined)
		Adhesion strengths	NPD (no performance determined)
		Ultimate tensile strength MD/CMD	250/>230 N/50 mm)
		Tear resistance MD/CMD	>150/>150(%)
		Elongation after artificial ageing MD/CMD	40/60 (%)
		Alkali resistance MD/CMD	NPD (No Performance determined)
		Durability with regard to water vapour permeability by ageing	Conform EN 13859-1

The performance of the product identified is in comformity with the set of declared performance/s. This declaration of performance is issued in accordance with (EU) No 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer.

B.M.D. van Kamperdijk, General Manager

Almelo, The Netherlands, 1 March 2018