Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 1/19



Opgesteld door: DB	Bekrachtigd door: GJL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Productname	Kelfort ® primer WB
Article numbere	1516071-156076
Producttype	Pre-treatment product

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Consumer use, Professional use, Industrial use
Use of substance/mixture	Undercoat
Uses advised against	No additional information available

1.3 Details of the supplier of the safety data sheet

Distributeur Ferney Group BV
Postbus 24
1700 AA Heerhugowaard – The Netherlands
T +31 (0)72-5765000 - F +31 (0)72-5765010
bedrijfsbureau@ferneygroup.nl - www.ferney.nl

1.4 Emergency telephone number

Noodtelefoon: +49(0)9366-907126 (ma-do 7.15-18.00 hour) or

: +31(0)30-2748888 (after worktime, exclusive use for doctors, pharmacists and government

institutions)

Country	Organisation/ Company	Address	Emergency number	Comments
The Netherlands	National Poisons Information Center	House post number B.00.118 PO Box 85500 3508 GA Utrecht	+31 30 274 88 88	For the sole purpose of informing healthcare professionals in the event of acute poisoning

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 2/19



Opgesteld door: DB Bekrachtigd door: GJL

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment - Chronic Hazard, H412

Category 3

Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do

EUH20

EUH20

1

not breathe spray or mist.

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) Not applicable

Hazard statements (CLP) H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) P102 - Keep out of reach of children.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or

international regulation.

[Spray application; P261 - Avoid breathing spray.]
EUH-statements
EUH208 - Contains 1,2-benzisothiazol-3(2H)-one; 1,2-

benzisothiazolin-3-one. May produce an allergic reaction.

EUH210 - Safety data sheet available on request.

EUH211 - Warning! Hazardous respirable droplets may be formed

when sprayed. Do not breathe spray or mist.

Child-resistant fastening Not applicable
Tactile warning Not applicable

2.3 Other hazards

Other hazards which do not result in classification: None under normal conditions.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 3/19



Opgesteld door: DB Bekrachtigd door: GJL

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Talc substance with national workplace exposure limit(s) (NL)	CAS-No.: 14807-96-6	2.5 - 10	Not classified
Mica;Silicates (less than 1% crystalline silica): Mica (respirable dust);Glimmer;Mica # Mica;Mika (tinjac, liskum);Mika # Mica; 云 母 粉 尘 # Mica dust substance with national workplace exposure limit(s) (GB)	CAS-No.: 12001-26-2 EC-No.: 310-127-6	1 - 2.5	Not classified
Zinc oxide substance with national workplace exposure limit(s) (BE, NL)	CAS-No.: 1314-13-2 EC-No.: 215-222-5 EC Index-No.: 030- 013-00-7 REACH-no: 01- 2119463881- 32	1 - 2.5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Dipropylene glycol n-butylether substance with national workplace exposure limit(s) (NL)	CAS-No.: 29911-28-2 EC-No.: 249-951-5 REACH-no: 01- 2119451543- 42	1 - 2.5	Not classified
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3- one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613- 088-00-6	0,005≤ C < 0,05	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3- one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613- 088-00-6	(0.05 ≤C < 100) Skin Sens. 1, H317

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 4/19



Opgesteld door: DB	Bekrachtigd door: GJL

Comments	This mixture contains \geq 1% titanium dioxide (CAS 13463-67-7). The
	Annex VI classification of Titanium dioxide does not apply to this mixture
	according to its Note 10
	There are no additional ingredients present which, within the current
	knowledge of the supplier and in the concentrations applicable, are
	classified as hazardous to health or the environment, are PBTs, vPvBs or
	Substances of equivalent concern, or have been assigned
	a workplace exposure limit and hence require reporting in this section.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aid measures general	In all cases of doubt, or when symptoms persist, seek medical attention. Never give
	anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.
First-aid measures after inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped,
	administer artificial respiration. Give nothing by mouth.
First-aid measures after skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water or use
	recognised skin cleanser. Do NOT use solvents or thinners.
First-aid measures after eye contact	Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes,
	holding the eyelids apart and seek medical advice.
First-aid measures after ingestion	If accidentally swallowed rinse the mouth with plenty of water (only if
	the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms/effects No information is on file to date regarding acute and/or delayed post-

exposure symptoms

and effects.

4.3 Indication of any immediate medical attention and special treatment needed

No additional information available.

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 5/19



Opgesteld door: DB	Bekrachtigd door: GJL

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	carbon dioxide (CO2), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2 Special hazards arising from the substance or mixture

Fire hazard	An impenetrable black smoke is produced in the event of a fire. Exposure
	to decomposition
	products may cause a health hazard. Appropriate breathing apparatus
	may be required.

5.3. Advice for firefighters

Precautiona	ry measures fire	Cool closed containers exposed to fire with water.
Other inform	mation	Do not allow run-off from fire fighting to enter drains or water courses.

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 6/19



Opgesteld door: DB	Bekrachtigd door: GJL

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Protective equipment	Use personal protective equipment as required.
Emergency procedures	Do not smoke. Ventilate area. Do not breathe vapours.
Protective equipment	Equip rescue crew with proper protection.
Emergency procedures	No smoking. Ventilate area. Do not breathe vapours.

6.2 Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).
Other information	Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 7/19



Opgesteld door: DB	Bekrachtigd door: GJL

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Keep container tightly closed. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. For personal protection see Section 8. Comply with the health and safety at work laws.
Hygiene measures	Smoking, eating and drinking should be prohibited in application area.

7.2 Conditionss for safe storage

Storage conditions	Store in accordance with local/national regulations.
Storage temperature	5 - 30 °C Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight
Information on mixed storage	Store separately from oxidising agents and strongly alkaline and strongly acidic materials.
Storage area	Prevent unauthorised access.
Special rules on packaging	Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

No additional information available.

Date: 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 8/19



Opgesteld door: DB Bekrachtigd door: GJL

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.1.1 National occupational exposure and biological limit values

Mica;Silicates (less than 1% crystalline silica): Mica (respirable dust);Glimmer;Mica # Mica;Mika (tinjac, liskum);Mika # Mica;云母粉尘 # Mica dust (12001-26-2)

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1] 10 mg/m³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2 Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general

extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

8.2.2. Personal protection equipment

Personal protective equipment:

Protective goggles. Gloves. In case of inadequate ventilation wear respiratory protection.

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Use safety eyewear designed to protect against splash of liquids.

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 9/19



Opgesteld door: DB	Bekrachtigd door: GJL

8.2.2.2. Skin protection

Skin and body protection:

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Every part of the skin which had contact with the product should have been washed thoroughly. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Wear overalls or long sleeved shirt. (EN 1149-1)

Hand protection:

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. For prolonged contact, use rubber or neoprene gloves. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

8.2.2.3. Respiratory protection

Respiratory protection:

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate

filter (EN 140).

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 10/19



Opgesteld door: DB Bekrachtigd door: GJL

SECTION 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	white. Grey.
Odour	Characteristic.
Odour threshold	Not available
pH	8 - 9 (ISO 19396-1:2017)
Relative evaporation rate	Not available
(butylacetate=1)	
Melting point	0 °C (Published data)
Freezing point	0 °C (Published data)
Boiling point	100 °C (Published data)
Flash point	Not applicable
Auto-ignition temperature	Not relevant/applicable due to nature of the product.
Decomposition temperature	When exposed to heat, may decompose liberating hazardous gases
Flammability (solid, gas)	Not flammable in the presence of the following materials or conditions:
	open fire, sparks and static discharge, heat and shock and mechanical
	impact.
	Not highly flammable, but may catch fire if continuously exposed to flame
	or high
	temperature.
Vapour pressure	Not relevant/applicable due to nature of the product.
Relative vapour density at 20 °C	1 (Published data)
Relative density	Calculated value (ISO 2811-1:2016)
Density	$\approx 1.33 \text{ g/cm}^3 \text{ Calculated value (ISO 2811-1:2016)}$
Solubility	Miscible with water.
Partition coefficient n-octanol/water	Not applicable
(Log Pow)	
Partition coefficient n-octanol/water	Not applicable
(Log Kow)	
Viscosity, kinematic	1278 mm ² /s
Viscosity, dynamic	95 - 100 KU (Krebs Stormer) @20°C
Explosive properties	No dangerous reactions known.
Oxidising properties	No data available.
Explosive limits	No data available

9.2 Other information

No additional information available

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 11/19



Opgesteld door: DB	Bekrachtigd door: GJL

Rubriek 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5 Incompatible materials

See Heading 7.

10.6 Hazardous decompostions products

Such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

Date: 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 12/19



Opgesteld door: DB	Bekrachtigd door: GJL

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Zinc oxide (1314-13-2)	
LD50 oral rat	> 15000 mg/kg
LD50 oral	7950 mg/kg LD50 oral mouse

Zinc oxide (1314-13-2)	
LC50 Inhalation - Rat	> 5.7 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	> 5.7 mg/l/4h
Additional information	Not irritating to rabbits on cutaneous application (OESO 404). Not irritating to rabbits on ocular application (OESO 405)
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
LD50 oral	1020 mg/kg bodyweight
LD50 dermal	4115 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	100 mg/l

Skin corrosion/irritation : Not classified

pH: 8 - 9 (ISO 19396-1:2017)

Serious eye damage/irritation : Not classified

pH: 8 - 9 (ISO 19396-1:2017)

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified. Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-repeated exposure : Not classified Aspiration hazard : Not classified

p	
Kelfort Primer WB	
Viscosity, kinematic	1278 mm²/s

Potential adverse human health effects and symptoms

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 13/19



Opgesteld door: DB	Bekrachtigd door: GJL

SECTION 12: Ecological information

12.1 Toxicity

Ecology – general:	The mixture has been assessed following the conventional method of the Regulation (EC) No. 1272/2008 [CLP] and is classified as dangerous for the environment. See Sections 2 and 3 for details.
Hazardous to the aquatic environment, short–term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Harmful to aquatic life with long lasting effects.

Zinc oxide (1314-13-2)		
LC50 - Fish [1]	0.14 (0.14 - 0.169) mg/l 96 h., Oncorhynchus mykiss	
EC50 - Crustacea [1]	0.147 (0.147 - 0.17) mg/l 48 h.	
ErC50 algae	0.14 (0.14 - 0.17) mg/l 72 h., (Selenastrum capricornutum)	
NOEC chronic fish	(OECD 215, 28d)	
NOEC chronic crustacea	(OECD 211, 21d)	
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazol-3(2H)-one;	nzisothiazolin-3-one (2634-33-5)	
LC50 - Fish [1]	2.18 mg/l	
EC50 - Crustacea [1]	2.94 mg/l	
EC50 - Other aquatic organisms [1]	2.94 mg/l waterflea	
EC50 - Other aquatic organisms [2]	0.11 mg/l	
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)		
EC50 72h - Algae [1]	0.11 mg/l	
ErC50 algae	0.11 mg/l [Selenastrum capricornutum, 72h]	
NOEC (chronic)	1.2 mg/l	
NOEC chronic fish	0.21 mg/l	
NOEC chronic crustacea	1.7 mg/l	
NOEC chronic algae	0.04 mg/l	

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 14/19



Opgesteld door: DB	Bekrachtigd door: GJL

12.2 Persistence and degradability

Kelfort Primer WB	
Persistence and degradability	There are no data available on the preparation itself. May cause long-term adverse effects in the aquatic environment. This product has not been tested for biodegradation.
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
Biodegradation	> 80 %

12.3 Bioaccumulative potential

Kelfort Primer WB		
Partition coefficient n-octanol/water (Log Pow)	Not applicable	
Partition coefficient n-octanol/water (Log Kow)	Not applicable	
Bioaccumulative potential	There are no data available on the preparation itself.	
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)		
BCF - Fish [1]	6.95 (OECD 305)	
Partition coefficient n-octanol/water (Log Pow)	0.7	
Partition coefficient n-octanol/water (Log Kow)	0.7 (OECD 117)	

12.4 Mobility in soil

Kelfort Primer WB	
Ecology - soil	There are no data available on the preparation itself.

12.5 Result of PBT

Kelfort Primer WB

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6 Other adverse

Additional information : Product may not flow into sewer or superficial water

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 15/19



Opgesteld door: DB	Bekrachtigd door: GJL

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal recommendations	Dispose of this material and its container in a safe way. Use caution when handling empty containers/containers that have not been cleaned or rinsed. Empty containers or inner bag may contain some residual product. Avoid dispersal of spilt material and waste material and prevent contact with soil, waterways, drains and sewers.
European List of Waste (LoW) code	08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11 08 01 15* - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 16/19



Opgesteld door: DB	Bekrachtigd door: GJL

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN numbe	r			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper	shipping name			'
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport	hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing gı	roup			'
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environme	ental hazards	1	1	
	Not applicable	Not applicable	Not applicable	Not applicable

14.6 Special precautions for user

Special transport precautions	Transport within user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
	accident or spillage.

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

Date: 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 17/19



Opgesteld door: DB	Bekrachtigd door: GJL	

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

IBC code : Not determined.
Ship type : Not determined.
Pollution category : Not determined.

SECTION 15 Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1 EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : This product is not covered by the Seveso Directive.

DIRECTIVE 2004/42/EC on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products:

EU limit value for Kelfort Primer WB (cat. A/d): 130 g/l.

Kelfort Primer WB Contains max 20.00 g/l VOC.

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

15.1.2 National regulations

No additional information available

15.2 National precautions

No chemical safety assessment has been carried out

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 18/19



Opgesteld door: DB	Bekrachtigd door: GJL	

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
2	Hazards identification	Added	
3.2	Composition/information on ingredients	Modified	
8	Control parameters	Modified	
9	Physical and chemical properties	Added	
11	Toxicological information	Modified	
12.	Ecological information	Modified	
15	Seveso	Added	

Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.	
EUH210	Safety data sheet available on request.	
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.	

Full text of H- and EUH-statements:		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
H302	Harmful if swallowed.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	

Date : 10-01-2023

VVFK(E): 11/1516071 t/m 156076

Rev : A Page : 19/19



Opgesteld door: DB	Bekrachtigd door: GJL	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aquatic Chronic 3	H412	Calculation method
EUH208	EUH208	Calculation method
EUH211	EUH211	Calculation method

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.