




## Air Boy® Classic

Robust, impact-resistant and leakage free

Blowgun with bent pipe, ø8mm

The JWL ergonomic design is a classic in itself. We use the compressed air to ease the activation of the handle making it easy, precise and simple to operate.

The Air Boy® Classic is produced in an impact-resistant acetal plastic (POM)





The durability of our blowguns is top notch - even after 28 million operations. Therefore, we are also proud to offer you a 25 year warranty on the valve system in your Air Boy® blowgun!

Materials			Specifications			Directives			
Handle and trigger	Acetal plastic	<b>P</b>	Max 16 bar				2003/10/CE	Max 85 dB	ОК
Valve	Acetal plastic		380 l/min (8 bar)			0	OSHA 1910.95 (b)	Max 90 dB 8 hr	OK
Gaskets / O-rings	Nitrile		85 dB (8 bar), 84	dB (6 bar	bar)		OSHA STD 1-13.1	Max 30 psi when blocked	-
Blowing tube & shaft	Steel, el. galvanised		-10°C to +80°C						
Spring	Hardened spring wire		~0,105 kg						
Flow	l/min(cfm) / bar(psi)	Noise level			dB / bar(psi)	Blo	wing force	Newton (g) / ba	r(psi)
600 (21,19) 500 (17,66) 400 (14,13)		9	100 90 Measured at a distance of 1m to the side of the nozzle 80 85			6 (612) 5 Measured on a 400 x 400mm plate at a distance of 150 mm from the nozzle (408) 2.84			

60 50



200

100