



Ondervloer PE 2,0 alu 1x12,5 m²

Artikelnr. 114646
Technische Fiche - versie 2020.1

| # | PROPERTY | DIM | NORM | VALUE | |
|----|-------------------------|-------------------|------------|-------------------|---------|
| 1 | FOAM DENSITY | Kg/m ³ | DIN 53420 | 20 | ± 2 |
| 2 | FOAM THICKNESS | mm | | 2 | Nominal |
| 3 | WIDTH | mm | | As required | ± 5 |
| 4 | FILM THICKNESS | μ | | 12 | ± 3 % |
| 5 | TOTAL THICKNESS | mm | | 2,01 | Nominal |
| 6 | FLATNESS (after trim) | mm | | To be defined | |
| 7 | MARKING | | | To be defined | |
| 8 | TENSILE STRENGTH | N/mm ² | ASTM D 882 | 155 (L) – 210 (T) | |
| 9 | ELONGATION AT RUPTURE | % | ASTM D 882 | 84 (L) – 55 (T) | |
| 10 | Λ VALUE FOAM LAYER | W/m ^{°K} | DIN 52612 | 0,045 | |
| 11 | W.V.T.R. | g | ASTM E 398 | < 1,5 | |
| 12 | EMISSIVITY OF PET LAYER | | | 0,35 | |