

Winter Cut C Nitrile Foam Pro DTTS PSP 18-555

DESCRIPTION

The PSP 18-555 Winter Cut C Pro DT TS is a cut-resistant winter glove with a double-lined liner. The outer liner is a 15G Nylon / Polyester liner. The inner liner is a 10G brushed acrylic, which keeps the hand warm and is equipped with cut protection. The glove is fully coated with a special Nitrile foam coating with dots, making it ideal for working in oily and wet conditions.

This special Nitrile foam coating is extremely comfortable to wear and ensures warm and dry hands with extra grip due to the nitrile foam coating with dots. Moreover, this glove has an additional treatment which makes it Touch screen compatible and allows you to operate all kinds of digital devices without taking off the glove. Exactly what you can expect from this comfortable, warm glove.

Article PSP 18-555 is tested and certified in accordance with the European Regulation (EU) 2016/425 and EN standards. EN ISO 21420:2020 / EN388:2016+A1:2018 EN407:2020 and EN511:2006.


FEATURES

- ▲ Cut resistance according to ISO 13997: C
- Double-lined liner: outer liner: 15g Nylon/Polyester,
- inner liner: 10g brushed acrylic liner with cut resistant fiber A Nitrile foam coating with dots for extra grip
- Touchscreen functionality
- ▲ Fully coated
- ▲ Winter lining
- ▲ Good grip oily and wet environments
- Good dexterity
- Multifunctional use
- Certification according to: EN ISO 21420:2020 / EN388:2016+A1:2018 and EN407:2020 and EN511

CERTIFICATIONS



Abrasion resistance = 4 Blade cut resistance = 4 Tear resistance = 2 Puncture resistance = 1 C Cut ISO 13997 = C



Cut ISO 13997: The letter A to F indicates the cut resistance according to ISO 13997. X = Control not performed or not applicable

APPLICATIONS

Cold work environments | Demolition work | Assembly Offshore | (Scaffolding) Construction | Earth, road and water construction | Steel Industry | Transport & logistics | (Petro-) chemical industry





**Note! The degree of protection depends on the coating used

PRODUCT INFORMATIE

	Material	Liner: Nylon/Polyester. Inner liner: brushed acrylic liner with cut-resistant fiber Coating: Nitrile foam + dots + Touchscreen Nylon 30%, Polyester 25%, Acrylic 35% Fiber 10%
	Color	Black / Black
	Length (mm)	220-260 Depending on the size
1	Cuff	Elasticated, knit wrist

ORDER DETAILS

	Size	Item number	Packing Unit
	08 / M	2.01.18.555.08	6 x 12 (72 paar)
	09 / L	2.01.18.555.09	6 x 12 (72 paar)
	10 / XL	2.01.18.555.10	6 x 12 (72 paar)
	11 / XXL	2.01.18.555.11	6 x 12 (72 paar)



EN 511:2006

