

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 / 1516056-1516057
Rev : A
Page : 1/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Productname	Kelfort® Latex Wall Paint
Article numbere	1516056-1516057
Producttype	Wallpaint

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Consumer use, Professional use, Industrial use
Use of the substance/mixture	Industrial and decoration painting.
Uses advised against	No additional information available

1.3 Details of the supplier of the safety data sheet

Distributeur Ferney Group BV
Postbus 24
1700 AA Heerhugowaard – The Netherlands
T +31 (0)72-5765000 - F +31 (0)72-5765010
bedrijfsbureau@ferneygroup.nl - www.ferney.nl

1.4 Emergency telephone number

Noodtelefoon : +49(0)9366-907126 (ma-do 7.15-18.00 hour) or
: +31(0)30-2748888 (after worktime, exclusive use for doctors, pharmacists and government institutions)

Country	Organisation/ Company	Address	Emergency number	Comments
The Netherlands	National Poisons Information Center	House post number B.00.118 PO Box 85500 3508 GA Utrecht	+31 30 274 88 88	For the sole purpose of informing healthcare professionals in the event of acute poisoning

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 2/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction. EUH208

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EUH211

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP)	Not applicable
Hazard statements (CLP)	Not applicable.
Precautionary statements (CLP)	P102 - Keep out of reach of children. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, protective clothing, eye protection. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. [Spray application; P261 - Avoid breathing spray.]
EUH-statements	EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction. EUH210 - Safety data sheet available on request. EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Child-resistant fastening	Not applicable
Tactile warning	Not applicable

2.3 Other hazards

Other hazards which do not result in classification :None under normal conditions.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 3/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Talc substance with national workplace exposure limit(s) (NL)	CAS-No.: 14807-96-6	2,5 – 10	Not classified
Kaolin, calcined substance with national workplace exposure limit(s) (NL)	CAS-No.: 92704-41-1	2,5 – 10	Not classified
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3- one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	0,005 ≤ C < 0,05	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3- one and 2-methyl-2H-isothiazol-3-one (3:1) substance with national workplace exposure limit(s) (NL) (Note B)	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	0,00015 ≤ C < 0,0015	Acute Tox. 2 (Inhalation), H330 (ATE=0,33 mg/l/4h) Acute Tox. 2 (Dermal), H310 (ATE=75 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=59 mg/kg bodyweight) Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071

Specific concentration limits:

Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3- one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	(0,05 ≤ C < 100) Skin Sens. 1, H317

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 / 1516056-1516057
Rev : A
Page : 4/21



Opgesteld door: DB	Bekrachtigd door: GL
--------------------	----------------------

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS-No.: 55965-84-9	(0,0015 ≤ C ≤ 100) Skin Sens. 1A, H317
	EC Index-No.: 613-167-00-5	(0,06 ≤ C < 0,6) Eye Irrit. 2, H319
	REACH-no: 01-2120764691-48	(0,06 ≤ C < 0,6) Skin Irrit. 2, H315
		(0,6 ≤ C ≤ 100) Eye Dam. 1, H318 (0,6 ≤ C ≤ 100) Skin Corr. 1C, H314
Comments	This mixture contains ≥ 1% titanium dioxide (CAS 13463-67-7). The Annex VI classification of Titanium dioxide does not apply to this mixture according to its Note 10	

Note B : Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis. Full text of H- and EUH-statements: see section 16

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 5/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aid measures general	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.
First-aid measures after inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
First-aid measures after skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. If skin irritation or rash occurs: Get medical advice/attention. Thoroughly clean shoes before re-using.
First-aid measures after eye contact	Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
First-aid measures after ingestion	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms/effects	No information is on file to date regarding acute and/or delayed post-exposure symptoms and effects.
------------------	--

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Immediate specific treatment is necessary in case of poisoning.

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 / 1516056-1516057
Rev : A
Page : 6/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media :carbon dioxide (CO2), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media :Do not use a heavy water stream.

5.2 Special hazards arising from the substance or mixture

Fire hazard :An impenetrable black smoke is produced in the event of a fire.
Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

5.3. Advice for firefighters

Precautionary measures fire :Cool closed containers exposed to fire with water.
Other information :Do not allow run-off from fire fighting to enter drains or water courses.

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 7/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment :No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. Do not touch or walk on the spilled product. Wear suitable protective clothing, gloves and eye/face protection.

Emergency procedures :Do not smoke. Ventilate area. Do not breathe vapours.

6.1.2. For emergency responders

Protective equipment :Equip rescue crew with proper protection.

Emergency procedures :No smoking. Ventilate area. Do not breathe vapours.

6.2 Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Collect spillage.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up :Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Other information :Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 / 1516056-1516057
Rev : A
Page : 8/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Precautions for safe handling :Keep container tightly closed. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Never use pressure to empty : container is not a pressure vessel. Always keep in containers of same material as the original one. For personal protection see Section 8. Comply with the health and safety at work laws.

Hygiene measures :Smoking, eating and drinking should be prohibited in application area. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditionss for safe storage

Storage conditions :Store in accordance with local/national regulations.

Storage temperature 5 - 30 °C Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight

Information on mixed storage :Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

Storage area :Prevent unauthorised access.

Special rules on packaging :Containers which are opened must be carefully resealed and kept upright to prevent leakage. Do not store in open, inadequate, mislabeled packaging.

7.3 Specific end use(s)

No additional information available

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 9/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2 Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

8.2.2. Personal protection equipment

Personal protection equipment

Gloves. Protective clothing. In case of splash hazard: safety glasses.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Use safety eyewear designed to protect against splash of liquids. Protective goggles (EN 166)

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 10/21



Opgesteld door: DB

Bekrachtigd door: GL

8.2.2.2.. Skin protection

Skin and body protection:

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Every part of the skin which had contact with the product should have been washed thoroughly. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Wear overalls or long sleeved shirt. (EN 1149-1)

Hand protection:

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. For prolonged contact, use rubber or neoprene gloves. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

8.2.2.3. Respiratory protection

Respiratory protection:

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 140) .

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 11/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	Different colours.
Odour	Characteristic.
Odour threshold	Not available
pH	8 – 9 (ISO 19396-1:2017)
Relative evaporation rate (butylacetate=1)	Not available
Melting point	0 °C (Published data)
Freezing point	0 °C (Published data)
Boiling point	100 °C (Published data)
Flash point	Not relevant/applicable due to nature of the product.
Auto-ignition temperature	Not relevant/applicable due to nature of the product.
Decomposition temperature	When exposed to heat, may decompose liberating hazardous gases
Flammability (solid, gas)	Not flammable in the presence of the following materials or conditions: open fire, sparks and static discharge, heat and shock and mechanical impact. Not highly flammable, but may catch fire if continuously exposed to flame or high temperature.
Vapour pressure	Not relevant/applicable due to nature of the product.
Relative vapour density at 20 °C	1 (Published data)
Relative density	Calculated value (ISO 2811-1:2016)
Density	≈ 1,56 g/cm ³ Calculated value (ISO 2811-1:2016)
Solubility	Miscible with water.
Partition coefficient n-octanol/water (Log Pow)	Not applicable
Partition coefficient n-octanol/water (Log Kow)	No data available
Viscosity, kinematic	3846 mm ² /s
Viscosity, dynamic	5,5 – 6 Pa·s @ 20 °C [LC 3]
Explosive properties	Not explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. No unusual hazard in case of fire.
Oxidising properties	No data available.
Explosive limits	Not applicable

9.2 Other information

No additional information available

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 / 1516056-1516057
Rev : A
Page : 12/21



Opgesteld door: DB

Bekrachtigd door: GL

Rubriek 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5 Incompatible materials

Strong bases. Strong oxidizers. Strong acids.

10.6 Hazardous decompositions products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Combustion generates: Toxic gases. Carbon oxides (CO, CO₂). fume.

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 13/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

Kaolin, calcined (92704-41-1)

LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg bodyweight
LC50 Inhalation - Rat	> 2,19 mg/l

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

LD50 oral rat	59 - 64 mg/kg bodyweight
LD50 oral	59 mg/kg bodyweight
LD50 dermal rabbit	75 - 87,12 mg/kg bodyweight
LD50 dermal	> 75 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	0,33 mg/l/4h

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)

LD50 oral	1020 mg/kg bodyweight
LD50 dermal	4115 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	100 mg/l

Skin corrosion/irritation	Not classified	pH: 8 - 9 (ISO 19396-1:2017)
Serious eye damage/irritation	Not classified	pH: 8 - 9 (ISO 19396-1:2017)
Respiratory or skin sensitisation	Not classified	
Germ cell mutagenicity	Not classified	
Carcinogenicity	Not classified	
Reproductive toxicity	Not classified	
STOT-single exposure	Not classified	
STOT-repeated exposure	Not classified	
Aspiration hazard	Not classified	

Kelfort Latex Wall Paint

Viscosity, kinematic	3846 mm ² /s
----------------------	-------------------------

Potential adverse human health effects and symptoms

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVK(E) : 19 / 1516056-1516057
Rev : A
Page : 14/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 12: Ecological information

12.1 Toxicity

Ecology - general :The mixture has been assessed following the conventional method of the Regulation (EC) No. 1272/2008 [CLP] and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See Heading 3.

Hazardous to the aquatic environment, short-term (acute) :Not classified

Hazardous to the aquatic environment, long-term (chronic) :Not classified

Kaolin, calcined (92704-41-1)

LC50 - Fish [1]	> 1000 mg/l (Oncorhynchus mykiss)
EC50 - Crustacea [1]	> 700 mg/l
ErC50 algae	> 1000 mg/l
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
LC50 - Fish [1]	0,22 mg/l
EC50 - Crustacea [1]	0,12 (0,1 - 0,16) mg/l
EC50 - Other aquatic organisms [1]	0,126 mg/l waterflea
EC50 - Other aquatic organisms [2]	0,003 mg/l
EC50 72h - Algae [1]	0,048 mg/l
ErC50 algae	0,0375 (0,027 - 0,048) mg/l pseudokirchneriella subcapitata
NOEC chronic fish	(Oncorhynchus mykiss); 28 d
NOEC chronic crustacea	doorstroomtest, 21 d

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)

LC50 - Fish [1]	2,18 mg/l
EC50 - Crustacea [1]	2,94 mg/l
EC50 - Other aquatic organisms [1]	2,94 mg/l waterflea
EC50 - Other aquatic organisms [2]	0,11 mg/l
EC50 72h - Algae [1]	0,11 mg/l
ErC50 algae	0,11 mg/l [Selenastrum capricornutum, 72h]
NOEC (chronic)	1,2 mg/l
NOEC chronic fish	0,21 mg/l
NOEC chronic crustacea	1,7 mg/l
NOEC chronic algae	0,04 mg/l

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 15/21



Opgesteld door: DB

Bekrachtigd door: GL

12.2 Persistence and degradability

Kelfort Latex Wall Paint

Persistence and degradability | There are no data available on the preparation itself.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

Biodegradation | > 60 % 10 days

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)

Biodegradation | > 80 %

12.3 Bioaccumulative potential

Kelfort Latex Wall Paint

Partition coefficient n-octanol/water (Log Pow) | Not applicable

Partition coefficient n-octanol/water (Log Kow) | No data available

Bioaccumulative potential | There are no data available on the preparation itself.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

Bioconcentration factor (BCF REACH) | 3,16

Partition coefficient n-octanol/water (Log Pow) | 0,4

Partition coefficient n-octanol/water (Log Kow) | ≤ 0,71

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)

BCF - Fish [1] | 6,95 (OECD 305)

Partition coefficient n-octanol/water (Log Pow) | 0,7

Partition coefficient n-octanol/water (Log Kow) | 0,7 (OECD 117)

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 / 1516056-1516057
Rev : A
Page : 16/21



Opgesteld door: DB

Bekrachtigd door: GL

12.4 Mobility in soil

Kelfort Latex Wall Paint

Ecology - soil

There are no data available on the preparation itself.

**reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
(55965-84-9)**

Organic Carbon Normalized Adsorption
Coefficient (Log Koc)

28 (0 - 50)

12.5 Result of PBT

Kelfort Latex Wall Paint

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6 Other adverse

Additional information

Product may not flow into sewer or superficial water

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 17/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Regional legislation (waste)	Do not allow to enter drains or water courses.
Product/Packaging disposal recommendations	Dispose of this material and its container in a safe way. Use caution when handling empty containers/containers that have not been cleaned or rinsed. Empty containers or inner bag may contain some residual product. Avoid dispersal of spilt material and waste material and prevent contact with soil, waterways, drains and sewers.
European List of Waste (LoW) code	08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11 08 01 15* - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 / 1516056-1516057
Rev : A
Page : 18/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6 Special precautions for user

Special transport precautions	Transport within user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
-------------------------------	--

Overland transport	Not applicable
Transport by sea	Not applicable
Air transport	Not applicable
Inland waterway transport	Not applicable
Rail transport	Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

IBC code	Not determined.
Ship type	Not determined.
Pollution category	Not determined.

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 19/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 15 Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances
Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.
Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants
Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.
Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : This product is not covered by the Seveso Directive.

DIRECTIVE 2004/42/EC on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products:

EU limit value for Kelfort Latex Wall Paint (cat. A/a): 30 g/l.

Kelfort Latex Wall Paint Contains max 30,00 g/l VOC.

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

15.1.2. National regulations

No additional information available

15.2 National precautions

No chemical safety assessment has been carried out

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 20/21



Opgesteld door: DB

Bekrachtigd door: GL

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
2	Hazards identification	Added	
3.2	Composition/information on ingredients	Modified	
8	Control parameters	Modified	
9	Physical and chemical properties	Added	
11	Toxicological information	Modified	
12.	Ecological information	Modified	
15	Seveso	Added	

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
EUH071	Corrosive to the respiratory tract.
EUH208	Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2- benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.
EUH210	Safety data sheet available on request.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.

Safety data sheets Ferney Group BV

Date : 23-01-2023
VVFK(E) : 19 /1516056-1516057
Rev : A
Page : 21/21



Opgesteld door: DB	Bekrachtigd door: GL
--------------------	----------------------

H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:
--

EUH208	EUH208	Calculation method
EUH211	EUH211	Calculation method

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.