



KL-0050-510 A

Shock Absorber Piston Rod Tool Set



Product information EN
⚠ Read and understand before use!



www.gedore-automotive.com



GEDORE Automotive GmbH

Breslauer Straße 41
78166 - Donaueschingen
Postfach 1329
78154 Donaueschingen - GERMANY

☎ +49 (0) 771 / 8 32 23-0
☎ +49 (0) 771 / 8 32 23-90
✉ info.gam@gedore.com
🌐 gedore-automotive.com

GEDORE TOOLS, INC.

Only for USA, Canada & Mexico / Sólo para EE.UU., Canadá y México
Seulement pour les USA, le Canada et le Mexique
7187 Bryhawke Circle, Suite 700
North Charleston, SC 29418, USA

☎ +1-843 / 225 50 15
☎ +1-843 / 225 50 20
✉ info@gedoretools.com
🌐 gedore.com

Version 02/2023

Product description

KL-0050-510 A - Shock absorber piston rod tool set, Mercedes

Suitable for Mercedes C-Class (W203) and CLK (W209) front axle.

For loosening and tightening shock absorber piston rod nuts (groove nut).

Scope of delivery/single parts overview

Pos.	Part no.	Description	Qty.
A	KL-0056-52	Allen key, 7mm (waf)	1
B	KL-0050-51 A	Shock absorber pin wrench 19mm (waf)	1

Specifications

Pins: 2 pcs

Drive: 19 + 10mm (waf)

Allen key (waf): 7mm

Overall length: 100mm

⚠ Safety instructions and regulations!

- ✔ **Before using** the special tool, read and understand **all** warning and safety instructions and **follow** them for **safe use!**
- ✔ Work on electrical installations may **only** be carried out by appropriately **qualified personnel!**
- ✔ **Always** observe and adhere to **all** safety rules and regulations when working on electrical installations!
- ✔ Use the special tool **as intended**, and **always** carry out maintenance and repair work in compliance with the regulations on occupational safety and accident prevention as well as the vehicle manufacturer's instructions!
- ✔ **Before each use**, check the special tool **carefully** for damage, loose parts, or unauthorised modifications. **Never** use it if you notice any such deficiencies!
- ✔ **Always** wear your personal protective equipment (*such as safety goggles, protective gloves, safety shoes*) during work

