



TRIPLE QX ULTRA DIESEL 15W40 MINERAL

Document version: September 2nd 2020



Description

TQX ULTRA Diesel 15W40 is a high-performance mineral diesel engine oil formulated to deliver reliable performance in a broad range of heavy-duty applications. It is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines).

Performance-level

ACEA E7
API CI-4 / SL
Caterpillar ECF-1-a / ECF-2
Cummins CES 20077 / CES 20078
Detroit Diesel 93K215
Deutz DQC III-10
Global DHD-1
JASO DH-1
Mack EO-M Plus / EO-N
MAN 3275-1
MB 228.3
MTU Oil Category 2
Renault RLD-2
Volvo VDS-3

Packing units

ART.NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776112	1 L	12	-
TQX.521776111	5 L	4	-
TQX.521776115	20 L	1	-
TQX.521772116	199 L	1	-

Typicals

TEST	VALUE	
Density at 15°C	0.883	kg/l
Kinematic Viscosity at 40°C	99.7	mm ² /s
Kinematic Viscosity at 100°C	13.6	mm ² /s
Viscosity Index	136	
Pourpoint	-32	°C
Total Base Number	9.2	mgKOH/g